

# Empirical Mode Decomposition: Definition and application to non linear time series

**Paulo Gonçalves\***, Patrick Flandrin<sup>†</sup> and Gabriel Rilling<sup>†</sup>

**École Normale Supérieure de Lyon, France**

\*INRIA - LIP (UMR CNRS - ENS Lyon - UCB Lyon - INRIA 5668)

<sup>†</sup> Laboratoire de Physique (UMR 5672 CNRS)

“Nonlinear dynamical methods and time series analysis workshop”  
Udine (Italy), Aug. 29 – Sept. 1, 2006

# Outline

- EMD : principle & algorithmic definition
- Equivalent filter bank
- Frequency resolution / components separation
- A simple application to satellite image time series
- Concluding remarks

# Outline

- EMD : principle & algorithmic definition
- Equivalent filter bank
- Frequency resolution / components separation
- A simple application to satellite image time series
- Concluding remarks

# Outline

- EMD : principle & algorithmic definition
- Equivalent filter bank
- Frequency resolution / components separation
- A simple application to satellite image time series
- Concluding remarks



# Outline

- EMD : principle & algorithmic definition
- Equivalent filter bank
- Frequency resolution / components separation
- A simple application to satellite image time series
- Concluding remarks

# Outline

- EMD : principle & algorithmic definition
- Equivalent filter bank
- Frequency resolution / components separation
- A simple application to satellite image time series
- Concluding remarks

# Outline

- EMD : principle & algorithmic definition
- Equivalent filter bank
- Frequency resolution / components separation
- A simple application to satellite image time series
- Concluding remarks

# Principle

- **Objective** — Uniquely from the observation  $x(t)$ , get a AM-FM type decomposition:

$$x(t) = \sum_{k=1}^K a_k(t) \Psi_k(t)$$

with  $a_k(\cdot)$  amplitude modulating functions and  $\Psi_k(\cdot)$  oscillating functions.

- **Idea** — “signal = fast oscillations superimposed to slow oscillations”.
- **Operating mode** — (“EMD”, Huang et al., '98)
  - ① identify locally in time, the fastest oscillation
  - ② subtract it from the original signal
  - ③ iterate upon the residual

# Principle

- **Objective** — Uniquely from the observation  $x(t)$ , get a AM-FM type decomposition:

$$x(t) = \sum_{k=1}^K a_k(t) \Psi_k(t)$$

with  $a_k(.)$  amplitude modulating functions and  $\Psi_k(.)$  oscillating functions.

- **Idea** — “signal = fast oscillations superimposed to slow oscillations”.
- **Operating mode** — (“EMD”, Huang et al., '98)
  - ① identify locally in time, the fastest oscillation
  - ② subtract it from the original signal
  - ③ iterate upon the residual

# Principle

- **Objective** — Uniquely from the observation  $x(t)$ , get a AM-FM type decomposition:

$$x(t) = \sum_{k=1}^K a_k(t) \Psi_k(t)$$

with  $a_k(\cdot)$  amplitude modulating functions and  $\Psi_k(\cdot)$  oscillating functions.

- **Idea** — “signal = fast oscillations superimposed to slow oscillations”.
- **Operating mode** — (“EMD”, Huang et al., '98)
  - ① identify locally in time, the fastest oscillation
  - ② subtract it from the original signal
  - ③ iterate upon the residual

# Principle

- **Objective** — Uniquely from the observation  $x(t)$ , get a AM-FM type decomposition:

$$x(t) = \sum_{k=1}^K a_k(t) \Psi_k(t)$$

with  $a_k(\cdot)$  amplitude modulating functions and  $\Psi_k(\cdot)$  oscillating functions.

- **Idea** — “signal = fast oscillations superimposed to slow oscillations”.
- **Operating mode** — (“EMD”, Huang et al., '98)
  - ① identify locally in time, the fastest oscillation
  - ② subtract it from the original signal
  - ③ iterate upon the residual

# Principle

- **Objective** — Uniquely from the observation  $x(t)$ , get a AM-FM type decomposition:

$$x(t) = \sum_{k=1}^K a_k(t) \Psi_k(t)$$

with  $a_k(.)$  amplitude modulating functions and  $\Psi_k(.)$  oscillating functions.

- **Idea** — “signal = fast oscillations superimposed to slow oscillations”.
- **Operating mode** — (“EMD”, Huang et al., '98)
  - ① identify locally in time, the fastest oscillation
  - ② subtract it from the original signal
  - ③ iterate upon the residual



# Principle

- **Objective** — Uniquely from the observation  $x(t)$ , get a AM-FM type decomposition:

$$x(t) = \sum_{k=1}^K a_k(t) \Psi_k(t)$$

with  $a_k(\cdot)$  amplitude modulating functions and  $\Psi_k(\cdot)$  oscillating functions.

- **Idea** — “signal = fast oscillations superimposed to slow oscillations”.
- **Operating mode** — (“EMD”, Huang et al., '98)
  - ① identify locally in time, the fastest oscillation
  - ② subtract it from the original signal
  - ③ iterate upon the residual

# Principle




- **Objective** — Uniquely from the observation  $x(t)$ , get a AM-FM type decomposition:

$$x(t) = \sum_{k=1}^K a_k(t) \Psi_k(t)$$


with  $a_k(\cdot)$  amplitude modulating functions and  $\Psi_k(\cdot)$  oscillating functions.

- **Idea** — “signal = fast oscillations superimposed to slow oscillations”.
- **Operating mode** — (“EMD”, Huang et al., '98)
  - 1 identify locally in time, the fastest oscillation
  - 2 subtract it from the original signal
  - 3 iterate upon the residual


# Algorithm




## Algorithm - Sifting Process




## Algorithm - Sifting Process




## Algorithm - Sifting Process



## Algorithm - Sifting Process




## Algorithm - Sifting Process








## Algorithm - Sifting Process




## Algorithm - Sifting Process




## Algorithm - Sifting Process




Is this an IMF ?




## Algorithm - Sifting Process




## Algorithm - Sifting Process




## Algorithm - Sifting Process



## Algorithm - Sifting Process




## Algorithm - Sifting Process








## Algorithm - Sifting Process




## Algorithm - Sifting Process




## Algorithm - Sifting Process




Is this an IMF ?




## Algorithm - Sifting Process




This is an IMF !




## Algorithm - Sifting Process




## Algorithm - Sifting Process



## Algorithm - Sifting Process




## Algorithm - Sifting Process








## Algorithm - Sifting Process




## Algorithm - Sifting Process




## Algorithm - Sifting Process




## Algorithm - Sifting Process




Is this an IMF ?




## Algorithm - Sifting Process




This is an IMF !




## Algorithm - Sifting Process



## Algorithm - Sifting Process




## Algorithm - Sifting Process







## Algorithm - Sifting Process





## Algorithm - Sifting Process




## Algorithm - Sifting Process




## Algorithm - Sifting Process




## Algorithm - Sifting Process




Is this an IMF ?




## Algorithm - Sifting Process




Is this an IMF ?




## Algorithm - Sifting Process




Is this an IMF ?



## Algorithm - Sifting Process




Is this an IMF ?







## Algorithm - Sifting Process




This is an IMF !




## Algorithm - Sifting Process



## Algorithm - Sifting Process




## Algorithm - Sifting Process



## Algorithm - Sifting Process


Insufficient number of extreme points



Residue !



## Algorithm - Sifting process



# Intrinsic Mode Function

## Definition

- 1  $\#\{\text{zero crossing}\} = \#\{\text{extrema}\} \pm 1$
- 2 symmetric envelopes around the  $y = 0$  axis

- Intrinsic Mode Functions (IMF) functions
- $\Rightarrow$  linear and nonlinear situations, and in nonlinear situations  
IMF = several Fourier modes
- Output of a  $\Rightarrow$  Hilbert transform  
( $\neq$  standard linear filter)
- illustration: 2 sinus FM + gaussian wave packet

# Intrinsic Mode Function

## Definition

- 1  $\#\{\text{zero crossing}\} = \#\{\text{extrema}\} \pm 1$
- 2 symmetric envelopes around the  $y = 0$  axis

- symmetrically oscillating functions
- $\text{IMF} \neq \text{Fourier mode}$ , and in nonlinear situations  
 $\text{IMF} = \text{several Fourier modes}$
- Output of a self-adaptive time-varying filter  
( $\neq$  standard linear filter)

illustration: 2 sinus FM + gaussian wave packet



# Intrinsic Mode Function

## Definition

- 1  $\#\{\text{zero crossing}\} = \#\{\text{extrema}\} \pm 1$
- 2 symmetric envelopes around the  $y = 0$  axis

- **symetrically oscillating functions**
- IMF  $\neq$  Fourier mode, and in nonlinear situations  
IMF = several Fourier modes
- Output of a self-adaptive time-varying filter  
( $\neq$  standard linear filter)

illustration: 2 sinus FM + gaussian wave packet

# Intrinsic Mode Function

## Definition

- 1  $\#\{\text{zero crossing}\} = \#\{\text{extrema}\} \pm 1$
- 2 symmetric envelopes around the  $y = 0$  axis

- symmetrically oscillating functions
- IMF  $\neq$  Fourier mode, and in nonlinear situations  
IMF = several Fourier modes
- Output of a self-adaptive time-varying filter  
( $\neq$  standard linear filter)

illustration: 2 sinus FM + gaussian wave packet

# Intrinsic Mode Function


## Definition

- 1  $\#\{\text{zero crossing}\} = \#\{\text{extrema}\} \pm 1$
- 2 symmetric envelopes around the  $y = 0$  axis



- symmetrically oscillating functions
- $\text{IMF} \neq \text{Fourier mode}$ , and in nonlinear situations  
IMF = several Fourier modes
- Output of a self-adaptive time-varying filter  
( $\neq$  standard linear filter)

illustration: 2 sinus FM + gaussian wave packet


# Self-adaptive filter




## Self-adaptive filter






## Self-adaptive filter






How to separate these time  
and frequency overlapping  
components ?



# Self-adaptive filter








# Self-adaptive filter





# Self-adaptive filter



# IMF - A mathematical Approach (Vatchev, 2002)

## Definition

A twice differentiable function  $f$  is an IMF if it is a solution of the self-adjoint ODE:

$$(Pf')' + Qf = 0$$

with  $P(t) > 0$  and  $Q(t) > 0$  for  $t \in [a, b]$

and

$$Q(t) = 1/P(t)$$

# IMF - A mathematical Approach (Vatchev, 2002)

## Definition

A twice differentiable function  $f$  is an IMF if it is a solution of the self-adjoint ODE:

$$(Pf')' + Qf = 0$$

with  $P(t) > 0$  and  $Q(t) > 0$  for  $t \in [a, b]$

and

$$Q(t) = 1/P(t)$$

# IMF - A mathematical Approach (Vatchev, 2002)

## Definition

A twice differentiable function  $f$  is an IMF if it is a solution of the self-adjoint ODE:

$$(Pf')' + Qf = 0$$

- with  $P(t) > 0$  and  $Q(t) > 0$  for  $t \in [a, b]$   
ensures that  $\#\{\text{zero crossings}\} = \#\{\text{extremes}\} \pm 1$

and

$$Q(t) = 1/P(t)$$

# IMF - A mathematical Approach (Vatchev, 2002)

## Definition

A twice differentiable function  $f$  is an IMF if it is a solution of the self-adjoint ODE:

$$(Pf')' + Qf = 0$$

with  $P(t) > 0$  and  $Q(t) > 0$  for  $t \in [a, b]$

and

- $Q(t) = 1/P(t)$

ensures that upper and lower envelopes  $U(t)$  and  $L(t)$  are symmetric

## IMF - A mathematical Approach (Vatchev, 2002)

### Theorem

*If  $f$  is solution of a self-adjoint ODE, with*

$$Q(t) = 1/P(t) > 0$$

*then  $f$  is an oscillating function with constant amplitude  
(harmonic function) !*

In practice, to overcome the envelope restriction:

- require that  $|U(t) - L(t)| < \varepsilon$ , for some prescribed  $\varepsilon > 0$
- change the envelope definition (???)

## IMF - A mathematical Approach (Vatchev, 2002)

### Theorem

*If  $f$  is solution of a self-adjoint ODE, with*

$$Q(t) = 1/P(t) > 0$$

*then  $f$  is an oscillating function with constant amplitude  
(harmonic function) !*

In practice, to overcome the envelope restriction:

- require that  $|U(t) - L(t)| < \varepsilon$ , for some prescribed  $\varepsilon > 0$
- change the envelope definition (???)

## IMF - A mathematical Approach (Vatchev, 2002)

### Theorem

*If  $f$  is solution of a self-adjoint ODE, with*

$$Q(t) = 1/P(t) > 0$$

*then  $f$  is an oscillating function with constant amplitude  
(harmonic function) !*

In practice, to overcome the envelope restriction:

- require that  $|U(t) - L(t)| < \varepsilon$ , for some prescribed  $\varepsilon > 0$
- change the envelope definition (???)



## IMF - A mathematical Approach (Vatchev, 2002)

### Theorem

*If  $f$  is solution of a self-adjoint ODE, with*

$$Q(t) = 1/P(t) > 0$$

*then  $f$  is an oscillating function with constant amplitude  
(harmonic function) !*

In practice, to overcome the envelope restriction:

- require that  $|U(t) - L(t)| < \varepsilon$ , for some prescribed  $\varepsilon > 0$
- change the envelope definition (???)

## IMF - A mathematical Approach (Vatchev, 2002)

### Theorem

*If  $f$  is solution of a self-adjoint ODE, with*

$$Q(t) = 1/P(t) > 0$$

*then  $f$  is an oscillating function with constant amplitude  
(harmonic function) !*

In practice, to overcome the envelope restriction:

- require that  $|U(t) - L(t)| < \varepsilon$ , for some prescribed  $\varepsilon > 0$
- change the envelope definition (???)

## Equivalent filter bank: a stochastic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent frequency response”

**Model** — fractional Gaussian noise (fGn – derivative of fractional Brownian motion fBm) with Hurst exponent  $0 < H < 1$ :

- $H = 1/2$  white Gaussian noise
- $H < 1/2$  short range correlation
- $H > 1/2$  long range correlation
- power spectral density (PSD)  
 $\sim f^{1-2H}$

**Simulations** — for  $H = 0.1$  to  $0.9$ , PSD of each IMF is estimated over a set of 1000 realizations of  $N = 512$  points

## Equivalent filter bank: a stochastic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent frequency response”

**Model** — fractional Gaussian noise (fGn – derivative of fractional Brownian motion fBm) with Hurst exponent  $0 < H < 1$ :

- $H = 1/2$  white Gaussian noise
- $H < 1/2$  short range correlation
- $H > 1/2$  long range correlation
- power spectral density (PSD)  
 $\sim f^{1-2H}$

**Simulations** — for  $H = 0.1$  to  $0.9$ , PSD of each IMF is estimated over a set of 1000 realizations of  $N = 512$  points

## Equivalent filter bank: a stochastic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent frequency response”

**Model** — fractional Gaussian noise (fGn – derivative of fractional Brownian motion fBm) with Hurst exponent  $0 < H < 1$ :

- $H = 1/2$  white Gaussian noise
- $H < 1/2$  short range correlation
- $H > 1/2$  long range correlation
- power spectral density (PSD)  
 $\sim f^{1-2H}$

**Simulations** — for  $H = 0.1$  to  $0.9$ , PSD of each IMF is estimated over a set of 1000 realizations of  $N = 512$  points


## Equivalent filter bank: a stochastic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent frequency response”


**Model** — fractional Gaussian noise (fGn – derivative of fractional Brownian motion fBm) with Hurst exponent  $0 < H < 1$ :

- $H = 1/2$  white Gaussian noise
- $H < 1/2$  short range correlation
- $H > 1/2$  long range correlation
- power spectral density (PSD)  
 $\sim f^{1-2H}$

fBm -  $H = 0.2$



fGn -  $H = 0.2$



**Simulations** — for  $H = 0.1$  to  $0.9$ , PSD of each IMF is estimated over a set of 1000 realizations of  $N = 512$  points


## Equivalent filter bank: a stochastic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent frequency response”


**Model** — fractional Gaussian noise (fGn – derivative of fractional Brownian motion fBm) with Hurst exponent  $0 < H < 1$ :

- $H = 1/2$  white Gaussian noise
- $H < 1/2$  short range correlation
- $H > 1/2$  long range correlation
- power spectral density (PSD)  
 $\sim f^{1-2H}$

fBm -  $H = 0.5$



fGn -  $H = 0.5$



**Simulations** — for  $H = 0.1$  to  $0.9$ , PSD of each IMF is estimated over a set of 1000 realizations of  $N = 512$  points

## Equivalent filter bank: a stochastic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent frequency response”


**Model** — fractional Gaussian noise (fGn – derivative of fractional Brownian motion fBm) with Hurst exponent  $0 < H < 1$ :

- $H = 1/2$  white Gaussian noise
- $H < 1/2$  short range correlation
- $H > 1/2$  long range correlation
- power spectral density (PSD)  
 $\sim f^{1-2H}$

fBm -  $H = 0.8$



fGn -  $H = 0.8$



**Simulations** — for  $H = 0.1$  to  $0.9$ , PSD of each IMF is estimated over a set of 1000 realizations of  $N = 512$  points




# Equivalent filter bank: a stochastic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent frequency response”

**Model** — fractional Gaussian noise (fGn – derivative of fractional Brownian motion fBm) with Hurst exponent  $0 < H < 1$ :

- $H = 1/2$  white Gaussian noise
- $H < 1/2$  short range correlation
- $H > 1/2$  long range correlation
- power spectral density (PSD)  
 $\sim f^{1-2H}$




**Simulations** — for  $H = 0.1$  to  $0.9$ , PSD of each IMF is estimated over a set of 1000 realizations of  $N = 512$  points

## Equivalent filter bank: a stochastic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent frequency response”




**Model** — fractional Gaussian noise (fGn – derivative of fractional Brownian motion fBm) with Hurst exponent  $0 < H < 1$ :

- $H = 1/2$  white Gaussian noise
- $H < 1/2$  short range correlation
- $H > 1/2$  long range correlation
- power spectral density (PSD)  
 $\sim f^{1-2H}$






**Simulations** — for  $H = 0.1$  to  $0.9$ , PSD of each IMF is estimated over a set of 1000 realizations of  $N = 512$  points

## Equivalent filter bank: a stochastic approach






## Equivalent filter bank: a stochastic approach



### Result




$$S_{k',H}(f) = \rho_H^{(2H-1)(k'-k)} S_{k,H}(f), \text{ with } \rho_H \approx 2 : \text{dyadic filter bank}$$

# Equivalent filter bank: a stochastic approach



## Result

$$S_{k',H}(f) = \rho_H^{(2H-1)(k'-k)} S_{k,H}(f), \text{ with } \rho_H \approx 2 : \text{dyadic filter bank}$$



## Equivalent filter bank: a deterministic approach

Goal — Consider EMD as a filter bank and identify for each IMF an “equivalent impulse response”

Model — Impulse as the “*limit process*” of the sum

$$s(t) = \delta(t) + \epsilon n(t)$$

with  $n(t)$  a white Gaussian noise, and  $\epsilon \rightarrow 0^+$

Simulations — Compute the average mean for each IMF over a set of 1000 realizations of  $s(t)$  with  $N = 2048$  points

## Equivalent filter bank: a deterministic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent impulse response”

**Model** — Impulse as the “*limit process*” of the sum

$$s(t) = \delta(t) + \epsilon n(t)$$

with  $n(t)$  a white Gaussian noise, and  $\epsilon \rightarrow 0^+$

**Simulations** — Compute the average mean for each IMF over a set of 1000 realizations of  $s(t)$  with  $N = 2048$  points

## Equivalent filter bank: a deterministic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent impulse response”

**Model** — Impulse as the “*limit process*” of the sum

$$s(t) = \delta(t) + \epsilon n(t)$$

with  $n(t)$  a white Gaussian noise, and  $\epsilon \rightarrow 0^+$

**Simulations** — Compute the average mean for each IMF over a set of 1000 realizations of  $s(t)$  with  $N = 2048$  points



## Equivalent filter bank: a deterministic approach

**Goal** — Consider EMD as a filter bank and identify for each IMF an “equivalent impulse response”


**Model** — Impulse as the “*limit process*” of the sum

$$s(t) = \delta(t) + \epsilon n(t)$$


with  $n(t)$  a white Gaussian noise, and  $\epsilon \rightarrow 0^+$

**Simulations** — Compute the average mean for each IMF over a set of 1000 realizations of  $s(t)$  with  $N = 2048$  points

## Equivalent filter bank: a deterministic approach




## Equivalent filter bank: a deterministic approach



$$\text{IMF}_k = a^k \psi(a^k t)$$


Wavelet-like multiresolution analysis

## Equivalent filter bank: a deterministic approach



$$\text{IMF}_k = a^k \psi(a^k t)$$

Wavelet-like multiresolution analysis



## Frequency resolution

Problem — When can EMD separate pure tones in a sum

$$s(t) = \sum_{k=1}^{k=M} a_k \sin(\omega_k t + \phi_k)$$

Obvious exceptions — Fourier series

Model — A sum of two sine waves  $s(t) = \underbrace{a_1 \sin(\omega_1 t)}_{s_1(t)} + \underbrace{a_2 \sin(\omega_2 t)}_{s_2(t)}$

$$0 \leq \omega_1 \leq \omega_2 \leq \dots \leq \omega_M \leq 1/\Delta t \leq \omega_{M+1} \leq \dots \leq 1/\Delta t$$

## Frequency resolution

**Problem** — When can EMD separate pure tones in a sum

$$s(t) = \sum_{k=1}^{k=M} a_k \sin(\omega_k t + \phi_k)$$

Obvious exceptions — Fourier series

**Model** — A sum of two sine waves  $s(t) = \underbrace{a_1 \sin(\omega_1 t)}_{s_1(t)} + \underbrace{a_2 \sin(\omega_2 t)}_{s_2(t)}$

## Frequency resolution

**Problem** — When can EMD separate pure tones in a sum

$$s(t) = \sum_{k=1}^{k=M} a_k \sin(\omega_k t + \phi_k)$$

**Obvious exceptions** — Fourier series

**Model** — A sum of two sine waves  $s(t) = \underbrace{a_1 \sin(\omega_1 t)}_{s_1(t)} + \underbrace{a_2 \sin(\omega_2 t)}_{s_2(t)}$


# Frequency resolution

**Problem** — When can EMD separate pure tones in a sum

$$s(t) = \sum_{k=1}^{k=M} a_k \sin(\omega_k t + \phi_k)$$

**Obvious exceptions** — Fourier series

Dirac time series



**Model** — A sum of two sine waves  $s(t) = \underbrace{a_1 \sin(\omega_1 t)}_{s_1(t)} + \underbrace{a_2 \sin(\omega_2 t)}_{s_2(t)}$




# Frequency resolution

**Problem** — When can EMD separate pure tones in a sum


$$s(t) = \sum_{k=1}^{k=M} a_k \sin(\omega_k t + \phi_k)$$

**Obvious exceptions** — Fourier series

Dirac time series



Dirac spectrum



**Model** — A sum of two sine waves  $s(t) = \underbrace{a_1 \sin(\omega_1 t)}_{s_1(t)} + \underbrace{a_2 \sin(\omega_2 t)}_{s_2(t)}$


# Frequency resolution

**Problem** — When can EMD separate pure tones in a sum


$$s(t) = \sum_{k=1}^{k=M} a_k \sin(\omega_k t + \phi_k)$$

**Obvious exceptions** — Fourier series

Dirac time series



Dirac spectrum



**Model** — A sum of two sine waves  $s(t) = \underbrace{a_1 \sin(\omega_1 t)}_{s_1(t)} + \underbrace{a_2 \sin(\omega_2 t)}_{s_2(t)}$

## Frequency resolution

**Problem** — When can EMD separate pure tones in a sum

$$s(t) = \sum_{k=1}^{k=M} a_k \sin(\omega_k t + \phi_k)$$

**Obvious exceptions** — Fourier series

**Model** — A sum of two sine waves  $s(t) = \underbrace{a_1 \sin(\omega_1 t)}_{s_1(t)} + \underbrace{a_2 \sin(\omega_2 t)}_{s_2(t)}$

- $0 < \omega_2 \leq \omega_1$  and  $a_1/4 \leq a_2 \leq 4a_1$
- Resolution measure (relative error)

$$e(\omega_1) = \frac{\|s_1(t) - \text{imf}_1(t)\|_{l_2}}{\|s_2\|_{l_2}}$$

- Ignore sampling issues... ( $\omega_1 \ll \pi$ )


# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$


Confusion map

## Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map






# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map






# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




## Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$




Confusion map




# Frequency resolution

varying frequency  $\omega_2 \leq \omega_1$



Confusion map






# Frequency resolution


varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$

Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




## Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




## Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map






# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map






# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$




Confusion map




# Frequency resolution

varying amplitude  $a_1/4 \leq a_2 \leq 4a_1$



Confusion map



## Application to satellite image time series

Sensor — MODIS (NASA). Radiometric sensitivity measured in 7 spectral bands and 2 vegetation indices (NDVI, EVI)

Resolutions — Weekly aquired images at nominal spatial resolution of 500m at nadir. One full year pixels time series: *voxels*

Study area — 9 land cover classes

## Application to satellite image time series

**Sensor** — MODIS (NASA). Radiometric sensitivity measured in 7 spectral bands and 2 vegetation indices (NDVI, EVI)

**Resolutions** — Weekly aquired images at nominal spatial resolution of 500m at nadir. One full year pixels time series: *voxels*

**Study area** — 9 land cover classes



## Application to satellite image time series

**Sensor** — MODIS (NASA). Radiometric sensitivity measured in 7 spectral bands and 2 vegetation indices (NDVI, EVI)

**Resolutions** — Weekly aquired images at nominal spatial resolution of 500m at nadir. One full year pixels time series: *voxels*

**Study area** — 9 land cover classes

## Application to satellite image time series


- Sensor** — MODIS (NASA). Radiometric sensitivity measured in 7 spectral bands and 2 vegetation indices (NDVI, EVI)
- Resolutions** — Weekly aquired images at nominal spatial resolution of 500m at nadir. One full year pixels time series: *voxels*
- Study area** — 9 land cover classes

## Application to satellite image time series

**Sensor** — MODIS (NASA). Radiometric sensitivity measured in 7 spectral bands and 2 vegetation indices (NDVI, EVI)

**Resolutions** — Weekly acquired images at nominal spatial resolution of 500m at nadir. One full year pixels time series: *voxels*

**Study area** — 9 land cover classes  
Class averaged time series (NDVI)




## Application to satellite image time series

**Sensor** — MODIS (NASA). Radiometric sensitivity measured in 7 spectral bands and 2 vegetation indices (NDVI, EVI)

**Resolutions** — Weekly aquired images at nominal spatial resolution of 500m at nadir. One full year pixels time series: *voxels*

**Study area** — 9 land cover classes  
Class averaged time series (NDVI)




# Application to satellite image time series


**Sensor** — MODIS (NASA). Radiometric sensitivity measured in 7 spectral bands and 2 vegetation indices (NDVI, EVI)

**Resolutions** — Weekly aquired images at nominal spatial resolution of 500m at nadir. One full year pixels time series: *voxels*

**Study area** — 9 land cover classes  
Class averaged time series (NDVI)



Single voxel




## Application to satellite image time series

**Sensor** — MODIS (NASA). Radiometric sensitivity measured in 7 spectral bands and 2 vegetation indices (NDVI, EVI)

**Resolutions** — Weekly acquired images at nominal spatial resolution of 500m at nadir. One full year pixels time series: *voxels*

**Study area** — 9 land cover classes  
Class averaged time series (NDVI)




Single voxel




# Application to satellite image time series

Annual time series



## Application to satellite image time series

Periodized time series




Assume **cyclo-stationarity** for time series



# Application to satellite image time series


Periodized time series




Linear low-pass filters do not preserve **non-linear responses**

# Application to satellite image time series

Periodized time series




EMD: IMFs and residue




Perform a **full EMD** of periodized data

# Application to satellite image time series

Periodized time series




EMD: IMFs and residue




Keep only the **one-year period IMF** and residue

## Application to satellite image time series

Periodized time series




EMD: IMFs and residue




Use **partial reconstruction** as denoised signal

# Application to satellite image time series

## Periodized time series



## EMD: IMFs and residue



Fit with a **non linear model**:

$$s(t) = \mu + A \cos(\Omega t + \psi + \alpha \cos(\Omega t + \varphi))$$

## Concluding remarks and open issues

### Assets

- ✓ *adaptive* — *totally data-driven decomposition*
- ✓ *local in time* — *appealing for non stationary processes*
- ✓ *nonlinear* — *efficient at stressing non harmonic oscillations*
- ✓ *multiscale* — *spontaneous dyadic filterbank structure*

### Drawbacks

- ✓ *adaptive* — *few degrees of freedom*
- ✓ *definition* — *consistency of an algorithm-based definition?*
- ✓ *theory* — *mathematical framework beyond numerical simulation: frustration, challenge...*

## Concluding remarks and open issues

### Assets

- ✓ *adaptive* — *totally data-driven decomposition*
- ✓ *local in time* — *appealing for non stationary processes*
- ✓ *nonlinear* — *efficient at stressing non harmonic oscillations*
- ✓ *multiscale* — *spontaneous dyadic filterbank structure*

### Drawbacks

- ✓ *adaptive* — *few degrees of freedom*
- ✓ *definition* — *consistency of an algorithm-based definition?*
- ✓ *theory* — *mathematical framework beyond numerical simulation: frustration, challenge...*

## Concluding remarks and open issues

### Assets

- ✓ *adaptive* — *totally data-driven decomposition*
- ✓ *local in time* — *appealing for non stationary processes*
- ✓ *nonlinear* — *efficient at stressing non harmonic oscillations*
- ✓ *multiscale* — *spontaneous dyadic filterbank structure*

### Drawbacks

- ✓ *adaptive* — *few degrees of freedom*
- ✓ *definition* — *consistency of an algorithm-based definition?*
- ✓ *theory* — *mathematical framework beyond numerical simulation: frustration, challenge...*



## Concluding remarks and open issues

### Assets

- ✓ *adaptive* — *totally data-driven decomposition*
- ✓ *local in time* — *appealing for non stationary processes*
- ✓ *nonlinear* — *efficient at stressing non harmonic oscillations*
- ✓ *multiscale* — *spontaneous dyadic filterbank structure*

### Drawbacks

- ✓ *adaptive* — *few degrees of freedom*
- ✓ *definition* — *consistency of an algorithm-based definition?*
- ✓ *theory* — *mathematical framework beyond numerical simulation: frustration, challenge...*

## Concluding remarks and open issues

### Assets

- ✓ *adaptive* — *totally data-driven decomposition*
- ✓ *local in time* — *appealing for non stationary processes*
- ✓ *nonlinear* — *efficient at stressing non harmonic oscillations*
- ✓ *multiscale* — *spontaneous dyadic filterbank structure*

### Drawbacks

- ✓ *adaptive* — *few degrees of freedom*
- ✓ *definition* — *consistency of an algorithm-based definition?*
- ✓ *theory* — *mathematical framework beyond numerical simulation: frustration, challenge...*

## Concluding remarks and open issues

### Assets

- ✓ *adaptive* — *totally data-driven decomposition*
- ✓ *local in time* — *appealing for non stationary processes*
- ✓ *nonlinear* — *efficient at stressing non harmonic oscillations*
- ✓ *multiscale* — *spontaneous dyadic filterbank structure*

### Drawbacks

- ✓ *adaptive* — *few degrees of freedom*
- ✓ *definition* — *consistency of an algorithm-based definition?*
- ✓ *theory* — *mathematical framework beyond numerical simulation: frustration, challenge...*

## Concluding remarks and open issues

### Assets

- ✓ *adaptive* — *totally data-driven decomposition*
- ✓ *local in time* — *appealing for non stationary processes*
- ✓ *nonlinear* — *efficient at stressing non harmonic oscillations*
- ✓ *multiscale* — *spontaneous dyadic filterbank structure*

### Drawbacks

- ✓ *adaptive* — *few degrees of freedom*
- ✓ *definition* — *consistency of an algorithm-based definition?*
- ✓ *theory* — *mathematical framework beyond numerical simulation: frustration, challenge...*