Loop parallelization algorithms: from parallelism extraction to code generation

Pierre Boulet Alain Darte Georges-André Silber
Frédéric Vivien
Laboratoire LIP, URA CNRS 1398
École Normale Supérieure de Lyon, F - 69364 LYON Cedex 07.
E-mail: FirstName.LastName@lip.ens-lyon.fr

Abstract

In this paper, we survey loop parallelization algorithms, analyzing the dependence representations they use, the loop transformations they generate, the code generation schemes they require, and their ability to incorporate various optimizing criteria such as maximal parallelism detection, permutable loops detection, minimization of synchronizations, easiness of code generation, etc. We complete the discussion by presenting new results related to code generation and loop fusion for a particular class of multi-dimensional schedules, called shifted linear schedules. We demonstrate that algorithms based on such schedules lead to simple codes.
Keywords: automatic parallelization, nested loops, parallelization algorithms, loop fusion, code generation.

1 Introduction

Loop transformations have been shown useful for extracting parallelism from regular nested loops for a large class of machines, from vector machines and VLIW machines to multiprocessor architectures. Several surveys have already presented in details the tremendous list of possible loop transformations (see for example the survey by Bacon, Graham and Sharp [4], or Wolfe's book [39]), and their particular use. Two additional surveys have presented the link between loop parallelization algorithms and dependence analysis: in [41], Yang, Ancourt and Irigoin characterize, for each loop transformation used to reveal parallelism, the minimal dependence abstraction needed to check its validity; in [17], a complementary study is proposed that answers the dual question: for a given dependence abstraction, what is the simplest algorithm that detects maximal parallelism?

Loop parallelization algorithms consist in finding a "good" loop transformation that reveals parallelism, but we must keep in mind that generating parallel loops is not sufficient for generating efficient parallel executable programs. When designing parallel loop detection algorithms, we must consider many other optimizations related to the granularity of

the parallel program, to the data distribution, to the communications, etc. For that, the algorithm must be *flexible enough* to incorporate criteria that are more accurate than the simple detection of parallel loops. Furthermore, the parallelizing algorithm is only a step in the whole compilation scheme: it should thus generate an intermediate abstract parallel code that is *simple enough* so that further optimizations can still be performed. For example, an algorithm for parallel loop detection can be integrated in a parallelization platform (as schematized in Figure 1) that transforms (automatically or semi-automatically) sequential Fortran to parallel Fortran via a language such as High Performance Fortran [22].



Figure 1: Parallelizing process

The aim of this paper is to survey loop parallelization algorithms with such a compilation scheme in mind. The first two sections of the paper (Sections 2 and 3) are devoted to a brief state of the art: in Section 2, we survey the different algorithms proposed in the literature, recalling the dependence representations they use, the loop transformations they generate, and their ability to incorporate optimizing criteria such as maximal parallelism detection, permutable loops detection, minimization of synchronizations, etc. In Section 3, we present the code generation techniques involved by these loop transformations. The last two sections present in more details some new contributions dealing with two particular optimization problems: how to generate codes that are as simple as possible (Section 4) and how to handle loop fusion (for example to minimize synchronizations) in loop parallelization algorithms (Section 5). Finally, we give some conclusions in Section 6.

Before that, we take the example of the compilation of High Performance Fortran to introduce some concepts and vocabulary, and to illustrate the kind of optimizations that remain to be done once parallel loops have been detected.

Consider the codes of Figure 2. Both have a single do loop, marked by the INDEPENDENT directive of HPF that asserts to the compiler that the iterations may be executed concurrently without changing the semantics of the program. There are no *dependences* between the different iterations of the loop or, in other words, there are no dependences *carried* by the loop. However, in the code (b) there is a *loop independent* dependence, from S_a to S_b for a given iteration of the loop.

Starting from the code in Figure 2(a), an HPF compiler may produce two types of code, following the *owner computes rule* (the processor that *owns* the left hand side of the

```
!HPF$ INDEPENDENT
do i = 1, N
   S_a : A[i] = B[i]
   S_b : C[i] = D[i]
enddo
```

(a)

```
!HPF$ INDEPENDENT
do i = 1, N
   S_a : A[i] = B[i]
   S_b : C[i - 1] = A[i]
enddo
```

(b)

Figure 2: Two abstract parallel codes.

computation *computes* it). The first type is the simplest expression of the owner computes rule on the entire iteration space. For each element of computation, the code tests if this element of computation is owned by the executor. This gives a parallel code like the one in Figure 3(a). To make this code more efficient, communications can be moved outside of the loop if array accesses are known at compile-time, or if the data have been already sent for a previous set of loops. Nevertheless, it remains inefficient since each processor spans the entire iteration space. If the code to compile is simple enough (as here) and if the compiler is smart enough, a second approach is possible in which each processor computes only the slice of the array it owns, as in the code of Figure 3(b). Note that the *distribution* of the code in two loops is not needed if both slices are the same, for example if both arrays are mapped the same way.

```
do i = 1, N
   if is_local(B[i]) send(B[i])
   if is_local(A[i]) A[i] = receive(B[i])

   if is_local(D[i]) send(D[i])
   if is_local(C[i]) C[i] = receive(D[i])
enddo
```

(a)

```
(Communication : get slice of B)
(Communication : get slice of D)
do i = my_A_slice_start, my_A_slice_stop
   A[i] = B[i]
enddo
do i = my_C_slice_start, my_C_slice_stop
   C[i] = D[i]
enddo
```

(b)

Figure 3: Two types of parallel executable codes for the code of Figure 2(a).

Now, consider the case where there is a loop independent dependence as in the code of Figure 2(b). A code such as the code in Figure 3(a) could also be generated. However, the communication of array A needed to compute array C cannot be just moved outside of the loop as before since we must communicate something that is computed *inside* the loop. A possibility is to distribute the loop to obtain the general scheme: a parallel loop, a global synchronization, a parallel loop. Another choice is to select a good mapping such that $A[i]$ and $C[i-1]$ are owned by the same processor, so that the loop independent dependence takes place inside a processor. In this case, we can even generate a code such as in Figure 4(b).

If A and C are not mapped to the same processor, these is a last possibility. Indeed, some compilers offer the ON HOME directive[1], modifying the owner computes rule. In the previous

[1]This directive is an approved extension of HPF 2.0 and some compilers have already implemented it, like ADAPTOR [8], an HPF compiler by Thomas Brandes.

```
do i = 1, N
   if is_local(B[i]) send(B[i])
   if is_local(A[i])
      A(i) = receive(B[i])
      send(A[i])
   endif
   if (is_local(C[i - 1]) C[i - 1] = receive(A[i])
enddo
```

(a)

```
(Communication : get slice of B)
do i = my_A_slice_start, my_A_slice_stop
   A[i] = B[i]
   C[i - 1] = A[i]
enddo
```

(b)

Figure 4: Two types of parallel executable codes for the code of Figure 2(b).

example, we can force the compiler to produce a code that computes $C[i-1]$ at the same place as $A[i]$, by generating temporary arrays or by duplicating some computations with the help of some overlap areas (as ADAPTOR does). This kind of code can be much more difficult to produce, because the compiler needs to have a precise knowledge of array accesses in order to produce the communications. One could argue that, in this case, a compiler should always compile a parallel loop with multiple statements as a succession of parallel loops with a single statement, interleaved with some communications/synchronizations. However, loop fusion (opposed to loop distribution) offers some other advantages (see Section 2) and it may be desirable to produce codes with large loop bodies.

This brief discussion shows that even with an INDEPENDENT directive, the actual generation of the parallel code has a variable degree of difficulty. The way parallel loops are exposed (fused or not fused for example) interfers with the different optimizations that are done (or that are not done!) before or after the generation of parallel loops (choice of the data mapping, generation of communications, of synchronizations, etc.). We will not describe these optimizations here. We refer to the survey in the same issue for a description of data mapping techniques.

2 Loop parallelization algorithms

The structure of nested loops allows the programmer to describe parameterized sets of computations as an enumeration, but in a particular order, called the sequential order. Many loop transformations have been proposed to change the enumeration order so as to increase the efficiency of the code, see for example the survey by Bacon, Graham and Sharp [4]. However, most of these transformations are still applied in an ad-hoc fashion, through heuristics, and only a few of them are generated fully automatically by loop parallelization algorithms.

In this section, we give a quick summary of the loop transformations that are captured by these loop parallelization algorithms (Section 2.2). Before, in Section 2.1, we recall the dependence abstractions used to check the validity of the transformations. Finally, in Section 2.3, we list the main loop parallelization algorithms that have been proposed in the literature, with a survey of their main characteristics (see Table 1).

All these algorithms apply to a particular type of code: nested loops, possibly non perfectly nested, but in which the control can be statically defined, in other words loops with no

jumps and no conditionals (except conditionals that can be captured statically, for example when control dependences can be converted to data dependences, or when the conditional restricts statically the range of the loop counters). Classically, loop bounds are supposed to be affine functions of some parameters and of surrounding loop counters, with unit steps, so that the computations associated to a given statement S can be described by a subset (actually the integral points of a polyhedron) D_S of $\mathbb{Z}^{n_S}$, where n_S is the number of loops surrounding S. D_S is called the *iteration domain* of S, and the integral vectors in D_S the *iteration vectors*. The i-th component of an iteration vector is the value of the counter of the i-th loop surrounding S, counting from the outermost to the innermost loop. To each $I \in D_S$ corresponds a particular execution of S denoted by $S(I)$. In the sequential order, all computations $S(I)$ are executed following the lexicographical order defined on the iteration vectors. If I and J are two vectors, we write $I \prec_{lex} J$ if I is lexicographically strictly smaller than J, and $I \preceq_{lex} J$ if $I \prec_{lex} J$ or $I = J$.

2.1 Dependence abstractions

Data dependence relations between operations are defined by Bernstein's conditions [5]. Two operations are dependent if both operations access the same memory location and if at least one access is a write. The dependence is directed according to the sequential order, from the first executed operation to the last one. We write $S(I) \longrightarrow S'(J)$ if the statement S' at iteration J depends on the statement S at iteration I. Dependences are captured through a directed acyclic graph, called the *reduced dependence graph* (RDG), or statement level dependence graph. Each vertex of the RDG is identified with a statement of the loop nest, and there is an edge from S to S' if there exists at least one pair $(I, J) \in D_S \times D_{S'}$ such that $S(I) \longrightarrow S'(J)$. An edge between S and S' is labeled using various *dependence abstractions* or *dependence approximations*, depending on the dependence analysis and on the input needed by the loop parallelization algorithm. Except for affine dependences (see below), a dependence $S(I) \longrightarrow S'(J)$ is represented by an approximation of the *distance vector* $J - I$. If S and S' do not have the same domain, only the components of the vector $J - I$, that correspond to the $n_{S,S'}$ loops surrounding both statements, are defined. Classical representations of distance vectors (by increasing precision) are:

Dependence level: introduced by Allen and Kennedy in [1, 2]. A distance vector $J - I$ is approximated by an element l (the *level*) in $[1, n_{S,S'}] \cup \{\infty\}$, defined as ∞ if $J - I = 0$, or as the largest integer such that the $l - 1$ first components of the distance vector are zero. When $l = \infty$, the dependence is said *loop independent*, and *loop carried* otherwise.

Direction vector: first described by Lamport in [29], then by Wolfe in [38]. A set of distance vectors between S and S' is represented by a $n_{S,S'}$-dimensional vector, called the *direction vector*, whose components belong to $\mathbb{Z} \cup \{*\} \cup (\mathbb{Z} \times \{+, -\})$. Its i-th component is an approximation of the i-th component of the distance vectors: $z+$ means $\geq z$, $z-$ means $\leq z$, and $*$ means any value.

Dependence polyhedron: introduced by Irigoin and Triolet [27]. A set of distance vectors between S and S' is approximated by a subset of $\mathbb{Z}^{n_{S,S'}}$, defined as the integral points of a polyhedron. This is an extension of the direction vector abstraction.

Affine dependences: used by Feautrier [19] to express dependence relations when exact dependence analysis is feasible. A set of dependences $S(I) \longrightarrow S'(J)$ can be represented by an affine function f that expresses I in terms of J ($I = f(J)$) or the converse, subject to affine inequalities that restrict the range of validity of the dependence.

2.2 Loop transformations

We only focus here on the transformations that are captured by the loop parallelization algorithms presented in Section 2.3.

Statement reordering: the order of statements in a loop body is modified. Statement reordering is valid if and only if loop independent dependences are preserved.

Loop distribution: a loop, surrounding several statements, is split into several identical loops, each surrounding a subset of the original statements. The validity of loop distribution is related to the construction of the strongly connected components of the RDG (without considering dependences carried by an outer loop).

Unimodular loop transformations: a unimodular loop transformation is a change of basis (in $\mathbb{Z}^{n_S}$) applied on the iteration domain D_S. The computations are described through a new iteration vector $I' = UI$ where U is an integral matrix of determinant 1 or -1. Unimodular loop transformations are combinations of loop interchange, loop reversal, and loop skewing. A unimodular transformation U is valid if and only if $Ud \succ_{lex} 0$ for each non zero distance vector d.

Affine transformations: a general affine transformation defines a new iteration vector I' for each statement S by an affine function $I' = M_S I + \rho_S$. M_S is a non parameterized non singular square integral matrix of size n_S, and ρ_S is a possibly parameterized vector. The linear part may be unimodular or not. Such a transformation is valid if and only if $S(I) \longrightarrow S'(J) \Rightarrow M_S I + \rho_S \prec_{lex} M_{S'} J + \rho_{S'}$.

Tiling: tiling consists in rewriting a set of n loops into $2n$ loops, by defining *tiles* of size $(t_1, \ldots, t_n)$: the iteration vector $I = (i_1, \ldots, i_n)$ is transformed into the new iteration vector $I' = (i_1 \div t_1, \ldots, i_n \div t_n, i_1 \bmod t_1, \ldots, i_n \bmod t_n)$. A sufficient condition for tiling is that the n original loops are fully permutable.

2.3 Parallelization algorithms

In the following, the optimality of an algorithm has to be understood with respect to the dependence abstraction it uses. For example, the fact that Allen and Kennedy's algorithm is optimal for maximal parallelism detection means that a parallelization algorithm which takes as input the same information as Allen and Kennedy's algorithm, namely a representation of dependences by dependence level, cannot find more parallelism. However, it does not mean that more parallelism can not be detected if more information is exploited.

Lamport's algorithm [29] considers perfectly nested loops whose distance vectors are supposed to be uniform (constant) except for some fixed components. It produces a set of vectors, best known as "Lamport's hyperplanes", that form a unimodular matrix. Lamport

proposed an extension of this algorithm to handle statement reordering, extension which can also schedule independently the left- and right-hand sides of assignments. Lamport's algorithm is related to linear schedules (see [13]) and to multi-dimensional schedules.

Allen and Kennedy's algorithm [2] is based on the decomposition of the reduced dependence graph into strongly connected components. It uses dependences represented by levels, and transforms codes by loop distribution and statement reordering. It is optimal for maximal parallelism detection (see [16]). The minimization of synchronizations is considered through loop fusion (see Section 5.1). However, it is not really adapted (because of the inaccuracy of dependence levels) to the detection of outer parallelism and permutable loops.

Wolf and Lam's algorithm [37] is a reformulation of Lamport's algorithm to the case of direction vectors. It produces a unimodular transformation that reveals fully permutable loops in a set of perfectly nested loops. As a set of d fully permutable loops can be rewritten as one sequential loop and $d-1$ parallel loops, it can also detect parallel loops. The dependence abstraction it uses is sharper than the one in Allen and Kennedy's algorithm. However, the structure of the RDG is not considered. It is optimal for maximal parallelism detection if dependences are captured by direction vectors (and no dependence graph structure).

Feautrier's algorithm [20, 21] produces a general affine transformation. It can handle perfectly nested loops as well as non perfectly nested loops as long as exact dependence analysis is feasible. It relies on affine dependences. The affine transformation is built as a solution of linear programs obtained by the affine form of Farkas' lemma [36] applied to dependence constraint equations. Although Feautrier's algorithm is the most powerful algorithm for detecting innermost parallelism in loops with affine dependences, it is not optimal since it turns out that affine transformations are not sufficient. Moreover, it is not adapted, currently, to the detection of outer parallelism and permutable loops.

Darte and Vivien's algorithm [15] is a simplification of Feautrier's algorithm to the case of dependences represented by dependence polyhedra (an example being direction vectors). It also produces an affine transformation, but of a restricted form, called shifter linear schedule (see Section 4.1). It is optimal for maximal parallelism detection if dependences are approximated by dependence polyhedra. Since it is simpler than Feautrier's algorithm, more optimizing criteria can be handled: the detection of permutable loops and outer parallelism (see [14]), and the minimization of synchronizations through loop fusion (see Section 5.2). Furthermore, the code generation is simpler (see Section 4). However, it may find less parallelism than Feautrier's algorithm when exact dependence analysis is feasible because of its restricted choice of transformations.

Lim and Lam [31] is an extension of Feautrier's algorithm whose goal is to detect fully permutable loops and outer parallel loops. As Feautrier's algorithm, it relies on a description of dependences as affine dependences. It uses the affine form of Farkas' lemma and the Fourier-Motzkin elimination. Lim and Lam's algorithm has the same qualities and weaknesses as Feautrier's algorithm: it is, in theory, very powerful, but no guarantee is given concerning the easiness of code generation. Indeed, many solutions are equivalent relatively to the criteria they optimize: choosing the simplest solution is not explained in Lim and Lam's algorithm, and code generation is not addressed.

Algorithms	Dependence abstraction	Loop transformations	Maximal degree of //	Synchro. Fusion	Code generation	Tiling
Allen-Kennedy [2]	Dependence level Multiple statements Non perfect	Distribution	Optimal	Yes	Very easy	No
Wolf-Lam [37]	Direction vectors One statement Perfect	Unimodular	Optimal	No	Easy	Yes
Darte-Vivien [15]	Polyhedra Multiple statements Perfect	Shifted linear	Optimal	Partial yes	Quite easy	Yes
Feautrier [21]	Affine (exact) Multiple statements Non perfect	Affine	Sub-optimal	No	Complicated	No
Lim-Lam [31]	Affine (exact) Multiple statements Non perfect	Affine	Sub-optimal	?	?	Yes

Table 1: A comparison of various loop parallelizing algorithms.

3 Code generation

Once the program has been analyzed and some loop transformation has been found, it remains to generate the code corresponding to the transformed program. In the current section, we review the techniques that currently exist to handle this problem. We go from the simplest transformations to the most complicated ones. We skip in the discussion loop distribution and statement reordering for which code generation is straightforward. The problem can be viewed as generating some iteration code for polyhedra, affine images of polyhedra and unions of affine images of polyhedra. We follow this hierarchy in our discussion.

3.1 Unimodular transformations

Unimodular transformations apply to perfect loop nests whose iteration domains are convex polyhedra. They are important for code generation because they guarantee that, if the original iteration domain is a convex polyhedron, the iteration domain of the transformed loop nest is also a convex polyhedron. It means that the code generation problem simplifies to lexicographically scanning the integer points of a convex polyhedron. The second part of the code generation is to express the array access functions with respect to the new loop indices. Since a unimodular transformation is invertible (with integral inverse), this is easy.

We present now the two classical approaches for the polyhedron scanning problem: the Fourier-Motzkin pairwise elimination and the simplex algorithm.

Fourier-Motzkin elimination. Ancourt and Irigoin first proposed this technique in [3] and it has then been used in several prototype compilers [26, 34, 23]. The idea is to use a projection algorithm to find the loop bounds for each dimension. The polyhedron is represented as usually by a system of inequalities. At each step of the elimination, some inequalities are added to the system to build a "triangular" system where each loop index depends only on the previous loop indices and on parameters. As many inequalities can define a loop bound, we have to take the maximum of the lower loop bounds and the minimum of the upper loop bounds. Let us take an example: a square domain transformed by a combination of loop skewing and loop interchange $\binom{i'_1}{i'_2} = \left(\begin{smallmatrix}1 & 1\\ 1 & 0\end{smallmatrix}\right)\binom{i_1}{i_2}$ (see Figure 5). The system describing the transformed polyhedron and its transformation by the Fourier-Motzkin elimination of i'_2 are:

$$\begin{cases} 1 \leq i'_2 \leq n \\ 1 \leq i'_1 - i'_2 \leq n \end{cases} \xrightarrow[\text{elimination of } i'_2]{\text{Fourier-Motzkin}} \begin{cases} 2 \leq i'_1 \leq 2n \\ 1 \leq i'_2 \leq n \\ i'_1 - n \leq i'_2 \leq i'_1 - 1 \end{cases}$$

The main drawback of this algorithm is that it can generate redundant inequalities. Their elimination requires a powerful test also based on the Fourier-Motzkin elimination or on the simplex algorithm [23]. If some redundant inequalities are not removed, empty iterations may appear in the resulting loop nest, causing overhead. Although the Fourier-Motzkin elimination has super-exponential complexity for big problems, it remains fast for small problems, and works well in practice.

```
do i1 = 1, n                                  do i'1 = 2, 2n
    do i2 = 1, n      (i'1, i'2) = (1 1; 1 0)(i1, i2)      do i'2 = max(1, i'1 - n), min(n, i'1 - 1)
        ...          ------------------>          ...
    enddo                                         enddo
enddo                                         enddo
```

Figure 5: Unimodular example.

Simplex algorithm. The second approach to compute the loop bounds uses an extended version of the simplex algorithm: indeed one has to be able to solve parametric integer linear problems in rational numbers. This method has been proposed by Collard, Feautrier and Risset in [12] and has been used in at least three experimental parallelizers [7, 12, 25].

The basic idea is to build a polyhedra D_k for each loop index i_k in which outer indices are considered as parameters and to search for the extrema of i_k in D_k so as to find the loop bounds. It has been shown in [12] that this resolution can be done using PIP [18], a parametric dual simplex implementation, and that the result is expressed as the ceiling of the maximum of affine expressions for the lower bound and the floor of the minimum of affine expressions for the upper one. On the example of Figure 5, the result is the same.

This algorithm produces no empty iterations but may introduce floor and ceiling operations. The complexity of the simplex algorithm is exponential in the worst case but polynomial on the average and so also works well in practice. Chamski [10] addresses the problem of control overhead by replacing extrema operations by conditionals at the expense of code duplication.

3.2 Non-unimodular linear transformations

When dealing with non-unimodular transformations, the classical approach [30] is to decompose the transformation matrix into its Hermite normal form [36] to get back to the unimodular case. An algorithm based on column operations on an integral nonsingular matrix T transforms it into the product $HU(= T)$ where U is unimodular and H is a nonsingular, lower triangular, nonnegative matrix, in which each row has a unique maximum entry, which is its diagonal entry. Once the transformation U has been considered, it is easy to handle the matrix H: each diagonal element corresponds to a multiplication of the loop counter and can be coded with steps in the loop indices, and the other non-zero entries are shifts. Figure 6 shows the example of the transformation of a 2-D loop nest by $\left(\begin{smallmatrix} 2 & 0 \\ 1 & 3 \end{smallmatrix}\right)$.

```
do i1 = lb_i1, ub_i1                          do i'1 = 2lb_i1, 2ub_i1, 2
    do i2 = lb_i2, ub_i2                          do i'2 = i'1/2 + 3lb_i2, i'1/2 + 3ub_i2, 3
        ...                                           ...
    enddo                                         enddo
enddo                                         enddo
```

Figure 6: Non-unimodular example.

Xue presented in [40] another method to deal with non-unimodular transformations. It is based on Fourier-Motzkin elimination to compute the loop bounds and on Hermite decomposition to compute the steps and shifting constants.

3.3 Extensions

Perfect loop nests with one-dimensional shifted linear schedules. In [7], Boulet and Dion explain how to deal with affine transformations which share the same linear part and shift the first transformed loop index with constants, one constant for each statement in the body of the original loop nest. Moreover, they handle the case of rational schedules, transformations whose first dimension may have rational entries.

Non perfect loop nests with one-dimensional schedules. Collard presents in [11] a method to produce code when each statement of a non perfect loop nest has been assigned an affine one-dimensional schedule.

General affine case. Kelly, Pugh and Rosset present in [28] a method to generate code for the general affine case: a non perfect loop nest transformed with a possibly different affine transformation for each statement. Their transformation is based on the Presburger arithmetic implemented in the Omega library [35]. The problem is to be able to scan an arbitrary union of polyhedra. In the next section, we present a simpler code generation scheme for the case of shifted linear schedules.

4 Code generation for shifted linear schedules

In most real codes, the loop transformations needed to exploit parallelism are quite simple (combinations of distribution and interchange for example). When they are derived and applied with the help of the human (i.e. by hand or semi-automatically), particular cases can be identified and complicated cases can be avoided when possible. However, when the loop transformations are derived and applied by the parallelizing compiler itself (i.e. automatically), all cases of transformations have to be considered in the code generation step, even if the complicated cases will never occur: the consequence is that the resulting code may be unreadable (which is a drawback if the user wants to check what the compiler is doing) or just too complicated for further optimizations. Therefore, we believe that it is important, in a parallelizer:

- to generate simple transformations when possible (optimization in the scheduling step).
- to develop simpler code generation schemes for particular types of transformations (optimization in the code generation step).

In this section, we address these two points (the second point first) by studying in more details a particular class of loop transformations that we call *multi-dimensional shifted linear schedules*. We will illustrate our results with the example below.

Example 1: Consider two statements S and S' with the same iteration domain $\{1 \leq i, j, k \leq N\}$. Assume that $S(i,j,k)$ and $S'(i,j,k)$ are mapped, using a multi-dimensional schedule, respectively to $(i-j, i+j, i+j+2k)$ and $(i-j+1, i+j+2, k)$. A possibility is to generate the code of Figure 7. The code is not really simple, involving complex guards (with modulo operations), non unit loop steps, complicated loop bounds and array access functions. Nevertheless, it is already a bit optimized: a more naive approach would have kept both S and S' inside the same t_3 loop and all conditionals in this innermost loop. Furthermore, some natural but redundant conditionals such as $t_1 \leq n-1$ for statement S' have been removed.

```
do t1 = -n + 1, n
   do t2 = max(t1 + 2, -t1 + 2), min(t1 + 2n + 1, -t1 + 2n + 3)
      if t1 + t2 = 0 mod 2 and t1 + t2 ≤ 2n
         do t3 = t2 + 2, t2 + 2n, 2
            S((t1+t2)/2, (t2-t1)/2, (t3-t2)/2)
         enddo
      endif
      if t1 + t2 = 1 mod 2 and t2 + t1 ≥ 5
         do t3 = 1, n
            S'((t1+t2-3)/2, (t2-t1-1)/2, t3)
         enddo
      endif
   enddo
enddo
```

Figure 7: A code with modulo operations.

Such complicated codes may occur when trying to scan (i.e. describe by loops) an arbitrary union of polyhedra, either when scheduling simultaneously several statements whose iteration domains are different (non perfectly nested loops) or when scheduling several statements with different multi-dimensional schedules. However, when restricting to multi-dimensional shifted linear schedules, we can avoid this general scanning problem. We will show that, if all iteration domains are the same up to a translation (a typical example is when the original code is perfectly nested), then the code generation for such schedules is a lot simpler, and leads to cleaner and more readable codes. Indeed, the code generation can be seen as a hierarchical combination of loop distributions, loop bumpings (i.e. adding a constant to a loop counter), and matrix transformations, where each statement can be considered independently (thus avoiding the complicated problem of overlapping different polyhedra). Furthermore, we will show that given a shifted linear schedule σ, it is always possible to build an equivalent shifted linear schedule σ', equivalent in the sense that the nature of the loops (sequential, parallel or permutable) in the transformed code is preserved, and such that the matrix transformations involved for σ' are only unimodular transformations.

4.1 Shifted linear schedules

To make the discussion simpler, we consider that all iteration domains have the same dimension n (i.e. with the notations of Section 2, $n_S = n$ for all statements S) so that all iteration vectors and all matrices have the same size. As recalled in Section 2.2, a multi-dimensional affine schedule σ is defined for each statement S by an integral square nonsingular matrix M_S of size n and an integral vector ρ_S of size n. We write $\sigma = (M_S, \rho_S)$. The computation $S(I)$ associated to the iteration vector I before transformation is associated to the iteration vector $M_S I + \rho_S$ after transformation. A multi-dimensional function $\sigma = (M_S, \rho_S)$ is a valid schedule if and only if:

$$S(I) \longrightarrow S'(J) \Rightarrow M_S I + \rho_S \prec_{lex} M_{S'} J + \rho_{S'} \tag{1}$$

We say that a dependence $S(I) \longrightarrow S'(J)$ is *satisfied by σ at level k* if:

$$[M_S I + \rho_S][k-1] = [M_{S'} J + \rho_{S'}][k-1] \text{ and } [M_S I + \rho_S]_k < [M_{S'} J + \rho_{S'}]_k$$

where the notation $[M]_k$ denotes the k-th row of a matrix M, and the notation $[M][k]$ denotes the matrix whose rows are the first k rows of M.

Equation 1 guarantees that k is always well-defined: any dependence is satisfied at some level k, and for a unique k. We denote by $k_{S,S'}$ the maximal level at which some dependence between S and S' is satisfied, and by $c_{S,S'}$ the maximal level c such that $[M_S][c] = [M_{S'}][c]$.

Definition 1. A multi-dimensional affine schedule $\sigma = (M_S, \rho_S)$ is *shifted linear* if, for any statements S and S', $[M_S][k_{S,S'}] = [M_{S'}][k_{S,S'}]$, i.e. if $k_{S,S'} \leq c_{S,S'}$. In other words, a multi-dimensional affine schedule is shifted linear if S and S' have the same linear part for the outermost levels as long as there exists a dependence between S and S' not yet satisfied.

Note that, as recalled in Section 2.3, looking for such schedules is not penalizing if dependences are captured by a polyhedral approximation of distance vectors (for example direction vectors) and if the main objective is the detection of the maximal degree of parallelism.

4.2 Code generation scheme

Remember the code generation scheme for a single statement S. If the matrix M_S is not unimodular, we use the Hermite form $M_S = H_S U_S$ where U_S is unimodular, H_S non negative, lower triangular, and each non diagonal component of H_S is strictly smaller than the diagonal component of same row. Then, we transform the code first using U_S, then using the loop skewing H_S. Here, we have multiple statements, different matrices M_S, and different constants ρ_S, therefore we must apply a different unimodular transformation, a different loop skewing, and a different loop bumping for each statement. Fortunately, by construction of the Hermite form [36], it can be shown that:

$$[M_S][k] = [M_{S'}][k] \;\Rightarrow\; [H_S][k] = [H_{S'}][k] \text{ and } [U_S][k] = [U_{S'}][k]$$

Therefore, while all dependences between two statements S and S' are not satisfied, all loops that surround S and S' are the same (up to a constant): we just have to generate the codes

for S and S' separately, and to fuse the two codes into a single one until level $k_{S,S'}$. Then, for the remaining dimensions, since there are no more dependences between S and S', the two codes do not need to be perfectly matched: one can just write them one above the other, and the resulting code remains correct. In other words, in this restricted case, there is no need for a complicated algorithm for scanning an arbitrary union of polyhedra.

The code generation process is the following. We write $M_S = H_S U_S$ and $\rho_S = H_S q_S + r_S$ where q_S and r_S are integral vectors where each component of r_S is non negative and strictly smaller than the corresponding diagonal element of H_S (this decomposition is unique). Then, we decompose the transformation $\sigma_S : I \to M_S I + \rho_S$ in four steps, $\sigma_S^1 : I \to U_S I$, $\sigma_S^2 : I \to I + q_S$, $\sigma_S^3 : I \to H_S I$, $\sigma_S^4 : I \to I + r_S$: σ_S^1 is a unimodular transformation, σ_S^2 is a loop bumping, σ_S^3 is a loop skewing (and each loop step is equal to the corresponding diagonal component of H_S), and σ_S^4 consists simply in writing the code in the r_S-th position in the loop body. We point out that when H_S is diagonal, there is no need to really multiply the counter by the diagonal component: we can keep the original counter and avoid loop steps and floor functions. We will use this remark in Section 4.3.

Back to Example 1: We find the two unimodular transformations $U_S : (i,j,k) \to (i-j, j, j+k)$ and $U_{S'} : (i,j,k) \to (i-j, j, k)$, and the two skewing transformations $H_S : (i,j,k) \to (i, i+2j, i+2k)$ and $H_{S'} : (i,j,k) \to (i, i+2j, k)$. Furthermore $q_S = r_S = (0,0,0)$, and $q_{S'} = (1,0,0)$, $r_{S'} = (0,1,0)$. We first find the two intermediate codes of Figure 8 by applying the transformations U_S and $U_{S'}$, and the loop bumping by q_S and $q_{S'}$.

```
do t1 = -n+1, n-1
   do t2 = max(1, -t1+1),
           min(n, -t1+n)
      do t3 = t2+1, t2+n
         S(t1+t2, t2, t3-t2)
      enddo
   enddo
enddo
```

```
do t1 = -n+2, n
   do t2 = max(1, -t1+2),
           min(n, -t1+n+1)
      do t3 = 1, n
         S'(t1+t2-1, t2, t3)
      enddo
   enddo
enddo
```

Figure 8: Separate codes after unimodular transformation.

Then, we apply the loop skewings H_S and $H_{S'}$, and the displacements by r_S and $r_{S'}$. We get the two codes of Figure 9. The displacements are visualized by nop operations.

Finally, merging the two codes, we get the code of Figure 10. The "apparent holes" due to the non unimodularity (and that appear as modulo operations in the code of Figure 7) have been clearly identified thanks to the displacements r_S and $r_{S'}$: the code of Figure 10 is now more efficient. Notice also that the two conditionals $t_1 \leq n-1$ and $t_1 \geq -n+2$ could be removed since they are redundant with the other constraints. We just kept them to make the technique more understandable.

```
do t1 = -n + 1, n - 1
   do t2 = max(t1 + 2, -t1 + 2),
           min(t1 + 2n, -t1 + 2n), 2
      do t3 = t2 + 2, t2 + 2n, 2
         S((t1+t2)/2, (t2-t1)/2, (t3-t2)/2)
      enddo
      nop
   enddo
enddo
```

```
do t1 = -n + 2, n
   do t2 = max(t1 + 2, -t1 + 4),
           min(t1 + 2n, -t1 + 2n + 2), 2
      nop
      do t3 = 1, n
         S'((t1+t2)/2 - 1, (t2-t1)/2, t3)
      enddo
   enddo
enddo
```

Figure 9: Separate codes after loop skewing.

```
do t1 = -n + 1, n
   do t2 = max(t1 + 2, -t1 + 2), min(t1 + 2n, -t1 + 2n + 2), 2
      if t1 ≤ n - 1 and t2 ≤ -t1 + 2n
         do t3 = t2 + 2, t2 + 2n, 2
            S((t1+t2)/2, (t2-t1)/2, (t3-t2)/2)
         enddo
      endif
      if t1 ≥ -n + 2 and t2 ≥ -t1 + 4
         do t3 = 1, n
            S'((t1+t2)/2 - 1, (t2-t1)/2, t3)
         enddo
      endif
   enddo
enddo
```

Figure 10: Combination of the two codes.

4.3 Equivalent schedules and unimodularity

In terms of parallelism extraction, multi-dimensional schedules may be used for detecting either *parallel* and *sequential* loops, or *permutable* loops as a first step before tiling. We say that two schedules σ and σ' are *equivalent* if, in both transformed codes, the nature of the loops (parallel or sequential in the first case, permutable in the second case) is the same.

Let us analyze how dependences in the original code are transformed if we use the code generation process described in Section 4.2. If $S(I) \longrightarrow S'(J)$ is satisfied at level k:

$$\begin{array}{l} [U_S I + q_S]\,[k-1] = [U_{S'} J + q_{S'}]\,[k-1] \text{ and } [r_S]\,[k-1] = [r_{S'}]\,[k-1] \\ [U_S I + q_S]_k \leq [U_{S'} J + q_{S'}]_k \\ [U_S I + q_S]_k = [U_{S'} J + q_{S'}]_k \Rightarrow [r_S]_k < [r_{S'}]_k \end{array} \tag{2}$$

In other words, a dependence satisfied at level k is either *loop carried* at level k (when $[U_S I + q_S]_k < [U_{S'} J + q_{S'}]_k$), or *loop independent* at level k, and in this latter case $r_S < r_{S'}$. A loop at level k is then parallel in the transformed code, if there is no dependence carried at level k between any two statements surrounded by this loop. We point out that the nature of a dependence (loop carried or loop independent) is not fully specified by the schedule $\sigma = (M_S, \rho_S)$ itself, but depends on the way we write the code. For example, handling the constants ρ_S differently may change the nature of a dependence (but not the level at which it is *satisfied* which is fully specified by σ). Therefore, the equivalence of two schedules has to be understood with respect to the code generation we use. We have the following result:

Theorem 1. *For any shifted linear schedule $\sigma = (M_S, \rho_S)$, there exists a shifted linear schedule $\sigma' = (M'_S, \rho'_S)$, equivalent for parallel and sequential loops, and such that $M'_S = H'_S U'_S$ where H'_S is non-negative diagonal and U'_S unimodular.*

Proof. See the extended proof in [6]. We build σ' as follows. We write $H_S = K_S H'_S$ where H'_S is the diagonal matrix such that H'_S and H_S have the same diagonal. Then $\sigma' = (K_S^{-1} M_S, K_S^{-1} H_S q_S + r_S) = (H'_S U_S, H'_S q_S + r_S)$ is a shifted linear schedule equivalent for parallel and sequential loops. □

We now consider schedules used for detecting maximal blocks of permutable loops. A maximal block of nested loops, from level i to level j, is permutable in the transformed code if for all statements S and S' surrounded by these loops, for any dependence $S(I) \longrightarrow S'(J)$ satisfied at a level between i and j, the dependence distance is non negative, i.e.:

$$[M_S I + \rho_S]\,[i-1] = [M_{S'} J + \rho_{S'}]\,[i-1] \Rightarrow [M_S I + \rho_S]\,[j] \leq [M_{S'} J + \rho_{S'}]\,[j] \tag{3}$$

Once again, since we address only shifted linear schedules, we consider only blocks, surrounding statements S and S', whose maximal level j is smaller than $c_{S,S'}$.

Theorem 2. *For any shifted linear schedule $\sigma = (M_S, \rho_S)$, there exists a shifted linear schedule $\sigma' = (M'_S, \rho'_S)$, equivalent for permutable loops, and such that $M'_S = H'_S U'_S$ where U'_S is unimodular and H'_S is positive diagonal, with all entries equal to 1 except possibly for each last level of a block of permutable loops containing S.*

Proof. The technique is to define, for each statement S, a well chosen loop skewing G_S (see the construction in [6]) such that $G_S M_S = H'_S U'_S$. Then $\sigma' = (G_S M_S, \lfloor G_S \rho_S \rfloor)$ is a shifted linear schedule equivalent for permutable loops. □

When generating code for revealing permutable loops, we may want that permutable loops are perfectly nested. This is not the case with the code generation scheme proposed in Section 4.2 because of the constants r_S. Each time two statements have different values of r_S for the same loop, the resulting code is non perfectly nested (except of course at the innermost level). Therefore, for general affine schedules, we may need to enforce loops to be perfectly nested by not decomposing the constants ρ_S into q_S and r_S. However, the resulting code would be much more complicated. This is the reason why we impose in Theorem 2 that the components of H'_S are equal to 1, except for the last level of a block of permutable loops. Then, the code is easy to generate.

Back to Example 1: We assume that the first two dimensions correspond to a block of permutable loops. Applying our "unimodularization" technique to the initial schedule – $(i-j, i+j, i+j+2k)$ for S and $(i-j+1, i+j+2, k)$ for S' – we find the two loop skewing transformations $G_S : (i,j,k) \to (i, i+j, -i+k)$ and $G_{S'} : (i,j,k) \to (i, i+j, k)$ which lead to the schedule $(i-j, 2i, 2j+2k)$ for S and $(i-j+1, 2i+3, k)$ for S'. By construction, this schedule is equivalent for permutable loops. Actually, it is also equivalent for parallel and sequential loops. We get the final equivalent code of Figure 11: it is simpler and moreover, it reveals exactly the same amount of parallelism (in terms of loops).

```
do t1 = -n + 1, n
   do t2 = max(t1 + 1, 1), min(t1 + n, n + 1)
      if t1 ≤ n − 1 and t2 ≤ n /* note: first constraint could be removed */
         do t3 = t2 − t1 + 1, t2 − t1 + n
            S(t2, t2 − t1, t1 − t2 + t3)
         enddo
      endif
      if t1 ≥ −n + 2 and t2 ≥ 2 /* note: first constraint could be removed */
         do t3 = 1, n
            S'(t2 − 1, t2 − t1, t3)
         enddo
      endif
   enddo
enddo
```

Figure 11: Equivalent code for Example 1.

As noticed in Section 4.2, all loop steps are unit steps, and there is no use of floor or ceiling functions, even if the transformation is non unimodular. This is because the loop skewings (the Hermite forms of the schedule) are diagonal: there is no need to really multiply the loop counter by the diagonal component.

This study demonstrates that shifted linear schedules have nice properties: we can derive schedules that are guaranteed to be simple (thanks to the "unimodularization" process described above) and we can generate simple codes for them. We point out that this "unimodularization" property is not true for arbitrary multi-dimensional schedules.

5 Fusion of parallel loops

The advantages of loop fusion are well-known. First, synchronization is a costly operation. Therefore, minimizing the number of synchronizations is important. Fusing parallel loops is part of the answer as one synchronization is required after each parallel loop. Second, even if loop fusion increases the size of the loop, which can have a negative impact on cache and register performances, it can improve data reuse by moving references closer in time, making them more likely to still reside in cache or registers [39, 32]. Reuse provided by fusion can even be made explicit by using scalar replacement to place array references in a register. Furthermore, fusion decreases loop overhead, increasing the granularity of parallelism, and allowing easier scalar optimizations, such as subexpression elimination.

In this section, we recall how the fusion of parallel loops is handled in Allen and Kennedy's algorithm so as to reduce the number of synchronizations (see [9]). We show that the problem becomes much more difficult if loop bumping and loop fusion are combined. We show the NP-completeness of the problem, even in the simple case of uniform dependences, and we propose an integer linear programming method to solve it.

5.1 Fusion of parallel loops in Allen and Kennedy's algorithm

Consider a piece of code only composed of parallel loops. Consider the dependences that take place *inside* the code (in other words, if the code is surrounded by some loops, do not consider dependences carried by these loops), and in particular dependences between different loops (inter-dependences). The fusion of two parallel loops is valid and gives one parallel loop if there is no inter-dependence between these two loops, or if all inter-dependences become loop independent after fusion. Otherwise, the semantics of the code is not preserved or the loop produced is sequential. An inter-dependence that is not loop independent after fusion is called *fusion preventing*.

The technique to minimize the number of parallel loops after fusion is the following. The goal is to assign to each statement S a nonnegative integer $\pi(S)$ that indicates which parallel loop contains S after fusion. Let e be a dependence from statement S to statement S'. Then, after fusion, the loop containing S must appear, in the new loop nest, before the loop containing S': $\pi(S) \leq \pi(S')$. Furthermore, if this dependence is fusion preventing, S and S' cannot be in the same loop after fusion: $\pi(S) + 1 \leq \pi(S')$. To minimize the total number of parallel loops after fusion, we just have to minimize the label of the last loop, $\max_S \pi(S)$. To obtain the desired loop nest, we place in the same parallel loop all statements with the same value π, and parallel loops are ordered by increasing π. The formulation is

thus:

$$\begin{cases} \max_S \pi(S) \text{ s.t. } \pi(S) \geq 0 \text{ and} \\ \forall\ S \xrightarrow{e} S' \text{ s.t. } e \text{ is not fusion preventing,} & \pi(S) \leq \pi(S') \\ \forall\ S \xrightarrow{e} S' \text{ s.t. } e \text{ is fusion preventing,} & \pi(S) + 1 \leq \pi(S') \end{cases}$$

The reader can recognize a classical scheduling problem: $\pi(S)$ is the maximal weight of a dependence path ending in S, where the weight of an edge is defined as 1 if the edge is fusion preventing, and 0 otherwise. Therefore, a greedy algorithm is optimal and polynomial.

An extension of this technique has been proposed in [32] to handle both the fusion of parallel loops and the fusion of sequential loops. It consists in two steps. First the fusion of parallel loops is performed as above, except that additional fusion preventing edges are added each time there is a dependence path between two statements that goes through a sequential loop. Then, the similar technique is used for sequential loops. As noticed by Mc Kinley and Kennedy, the total number of loops may not be minimal, but the number of parallel loops is and, therefore, the number of synchronizations.

5.2 Fusion of parallel loops and shifted linear schedules

We now consider the particular case of the generation of parallel loops with shifted linear schedules (see Section 4.1). We suppose that k loops have already been generated, and that all the dependences are satisfied by these loops, except some dependences that form an acyclic graph G_a. The code generation technique proposed in Section 4.2 would generate the $n-k$ remaining loops, by placing each statement in a separate set of nested parallel loops so that the dependences of the acyclic graph are satisfied, at level k, as loop independent. Here, we want to do better. We want to generate as few parallel loops as possible and no sequential loops, in order to have, once again, the maximal parallelism while minimizing synchronizations.

We consider the case where one loop remains to be built ($k = n-1$): the general case is similar if we decide that two statements share all or none of their surrounding parallel loops. Once again, we try to place in the same parallel loop only statements for which the schedule is defined by the same linear part (shifted linear schedule). Practically, we are given a vector X that will be used to generate the last loop, and we try to generate constants ρ_S so as to fully define the schedule. If S and S' are to be placed in the same parallel loop, we must find two constants ρ_S and $\rho_{S'}$ such that, for each dependence $e:\ S(I) \rightarrow S'(J)$, $X(J-I)+\rho_{S'}-\rho_S = 0$, i.e. so that the dependence becomes loop independent. To make the link with Section 5.1, here we try to fuse more parallel loops using in addition loop bumping. This gives more freedom, but makes the optimal solution more difficult to find.

We assume that the dependences in G_a are uniform. We denote by $w(e)$ the quantity $X(J-I)$ associated with the edge e. Remark that when G_a is acyclic, if considered as an undirected graph, one can always choose the constants ρ_S so that all statements can be placed in the same parallel loop. On the other hand, if G_a has an (undirected) cycle, this may not be possible. Indeed, consider an undirected cycle in G_a, $C = \sum_{e \in C} \delta_e e$ where $\delta_e \in \{-1, 1\}$, i.e. a cycle that can use an edge backwards ($\delta_e = -1$) or forwards ($\delta_e = 1$). Define the weight of C as $w(C) = \sum_{e \in C} \delta_e w(e)$. If all dependences of C are transformed into

loop independent dependences, then $w(C) = 0$. Conversely, if $w(C) \neq 0$, then for at least one edge $e = (S_e, S'_e)$ of the cycle, S'_e has to be placed in a parallel loop after the parallel loop that surrounds S_e. This remark leads to the following integer linear program

$$\begin{cases} \max_S \pi(S) \text{ s.t. } \pi(S) \geq 0 \text{ and} \\ \forall\ e = (S_e, S'_e),\ \pi(S_e) \leq \pi(S'_e) \\ w(C) \neq 0 \Rightarrow \sum_{e \in C} \pi(S'_e) \geq 1 + \sum_{e \in C} \pi(S_e) \\ \text{for each undirected elementary cycle } C. \end{cases}$$

that solves the problem: $\pi(S)$ is the label of the parallel loop in which S should be placed. Indeed, by construction, the subgraph G'_a of G_a formed by the edges $e = (S_e, S'_e)$ for which $\pi(S_e) = \pi(S'_e)$ only contains undirected cycles C such that $w(C) = 0$. Therefore, one can build the desired constants ρ_S such that for all edge $e \in G'_a$, $w(e) + \rho_{S'_e} - \rho_{S_e} = 0$.

We point out that solving the linear program above is exponential for two reasons: first, the number of undirected elementary cycles can be exponential, and second, we use integer linear programming. Nevertheless, in practice, G_a is usually very small, thus the program is solvable in reasonable time. However, in theory, the problem is NP-complete, as stated by the following theorem.

Theorem 3. *Let G_a be an acyclic directed graph where each edge e has a weight $w(e) \in \mathbb{Z}$. Given an integer ρ_S for each vertex S, we define the quantity $w_\rho(e)$ for each edge $e = (S_e, S'_e)$ by $w_\rho(e) = 0$ if $w(e) + \rho_{S'_e} - \rho_{S_e} = 0$, and $w_\rho(e) = 1$ otherwise. The weight of a path is defined as the sum of the weights $w_\rho(e)$ of its edges. Then, finding values for ρ_S which minimize the maximal weight w_ρ of a path in G_a is NP-complete.*

Proof. The proof is by reduction of the fusion problem from the UET-UCT scheduling problem (Unitary Execution Time - Unitary Communication Time), see details in [6]. □

We illustrate the methods described in Sections 5.1 and 5.2 with the program of Figure 12. Because of the non zero dependences the simple fusion builds three different parallel loops (see Figure 13) when the fusion with loop bumping only builds two parallel loops. We show on this example (third code on Figure 13) that, using loop peeling, one can remove the "if" tests introduced by loop fusion. In fact this is always possible and easy as the tests we introduced are always simple functions of the loop bounds. The removal of "if" tests is especially useful when the iteration domains are large.

```
do i = 1, n
    a[i] = 1
    b[i] = 1
    c[i] = a[i-1] + b[i]
    d[i] = a[i] + b[i-1]
    e[i] = d[i] + d[i-1]
enddo
```



Figure 12: Original code and its dependence graph.

```
dopar i = 1, n
    a[i] = 1
    b[i] = 1
enddo
dopar i = 1, n
    c[i] = a[i-1] + b[i]
    d[i] = a[i] + b[i-1]
enddo
dopar i = 1, n
    e[i] = d[i] + d[i-1]
enddo
```

```
dopar i = 1, n+1
    if i ≤ n then a[i] = 1
    if 1 < i then b[i-1] = 1
    if i ≤ n then d[i] = a[i] + b[i-1]
enddo
dopar i = 1, n
    c[i] = a[i-1] + b[i]
    e[i] = d[i] + d[i-1]
enddo
```

```
a[1] = 1
d[1] = a[1] + b[0]
dopar i = 2, n
    a[i] = 1
    b[i-1] = 1
    d[i] = a[i] + b[i-1]
enddo
b[n] = 1
dopar i = 1, n
    c[i] = a[i-1] + b[i]
    e[i] = d[i] + d[i-1]
enddo
```

Figure 13: One optimal solution for simple fusion, and two for fusion with loop bumping.

6 Conclusion

We have proposed a comparative study of loop parallelization algorithms, insisting on the program transformations they produce, on the code generation scheme they need, and on their capabilities to incorporate various optimization criteria such as the detection of parallel loops, the detection of permutable loops, the minimization of synchronizations through loop fusion, and the easiness of code generation.

The simplest algorithm (Allen and Kennedy's algorithm) is of course not able to detect as much parallelism as the most complex algorithm (Feautrier's algorithm and its variants or extensions). However, the code generation it involves is straightforward and sharp optimizations such as the maximal fusion of parallel loops can be taken into account. For more complex algorithms, the loop transformations are obtained as solutions of linear programs, minimizing one criterion: no guarantee is given concerning the simplicity of the solution, or its quality with respect to a second optimization criterion. In other words, for complex algorithms, it remains to demonstrate that generating a "clean" solution is feasible. We gave some hints in this direction. We showed that, for algorithms based on shifted linear schedules, code generation is guaranteed to be simple, and that loop fusion can be handled (even if it can be expensive in theory).

A fundamental problem remains to be solved in the future: the link between parallelism detection and data mapping. Indeed, a parallel loop can be efficiently executed only if an adequate data mapping is proposed. This question is related to complex problems such as automatic alignment and distribution, scalar and array privatization, duplication of computations, etc.

References

[1] John R. Allen and Ken Kennedy. PFC: a program to convert Fortran to parallel form. Technical Report MASC-TR82-6, Rice University, Houston, TX, USA, 1982.

[2] John R. Allen and Ken Kennedy. Automatic translation of Fortran programs to vector form. *ACM Transactions on Programming Languages and Systems*, 9(4):491–542, October 1987.

[3] Corinne Ancourt and François Irigoin. Scanning polyhedra with DO loops. In *Proc. of the 3rd ACM SIGPLAN Symposium on Principles and Practice of Parallel Programming*, pages 39–50, April 1991.

[4] David F. Bacon, Susan L. Graham, and Oliver J. Sharp. Compiler transformations for high-performance computing. *ACM Computing Surveys*, 26(4), 1994.

[5] Arthur J. Bernstein. Analysis of programs for parallel processing. *IEEE Transactions on Electronic Computers*, 15:757–762, October 1966.

[6] Pierre Boulet, Alain Darte, Georges-André Silber, and Frédéric Vivien. Loop parallelization algorithms: from parallelism extraction to code generation. Technical Report 97-17, LIP, ENS-Lyon, France, June 1997.

[7] Pierre Boulet and Michèle Dion. Code generation in Bouclettes. In *Proceedings of the Fifth Euromicro Workshop on Parallel and Distributed Processing*, pages 273–280, London, UK, January 1997. IEEE Computer Society Press.

[8] Thomas Brandes. *ADAPTOR Programmer's Guide - Version 4.0*. German National Research Institute for Computer Science, March 1996.

[9] David Callahan. *A Global Approach to Detection of Parallelism*. PhD thesis, Dept. of Computer Science, Rice University, March 1987.

[10] Zbigniew Chamski. *Environnement logiciel de programmation d'un accélérateur de calcul parallèle*. PhD thesis, Université de Rennes, Rennes, France, 1993.

[11] Jean-François Collard. Code generation in automatic parallelizers. In Claude Girault, editor, *Proc. Int. Conf. on Application in Parallel and Distributed Computing. IFIP WG 10.3*, pages 185–194. North Holland, April 1994.

[12] Jean-François Collard, Paul Feautrier, and Tanguy Risset. Construction of DO loops from systems of affine constraints. *Parallel Processing Letters*, 5(3):421–436, September 1995.

[13] Alain Darte, Leonid Khachiyan, and Yves Robert. Linear scheduling is nearly optimal. *Parallel Processing Letters*, 1(2):73–81, 1991.

[14] Alain Darte, Georges-André Silber, and Frédéric Vivien. Combining retiming and scheduling techniques for loop parallelization and loop tiling. *Parallel Processing Letters*, 1997. Special issue, to appear. Also available as Tech. Rep. LIP, ENS-Lyon, RR96-34.

[15] Alain Darte and Frédéric Vivien. Optimal fine and medium grain parallelism detection in polyhedral reduced dependence graphs. In *Proceedings of PACT'96*, Boston, MA, October 1996. IEEE Computer Society Press.

[16] Alain Darte and Frédéric Vivien. On the optimality of Allen and Kennedy's algorithm for parallelism extraction in nested loops. *Journal of Parallel Algorithms and Applications*, 12(1-3):83–112, 1997. Special issue on Optimizing Compilers for Parallel Languages.

[17] Alain Darte and Frédéric Vivien. Parallelizing nested loops with approximation of distance vectors: a survey. *Parallel Processing Letters*, 1997.

[18] Paul Feautrier. Parametric integer programming. *RAIRO Recherche Opèrationnelle*, 22:243–268, September 1988.

[19] Paul Feautrier. Dataflow analysis of array and scalar references. *Int. J. Parallel Programming*, 20(1):23–51, 1991.

[20] Paul Feautrier. Some efficient solutions to the affine scheduling problem, part I: one-dimensional time. *Int. J. Parallel Programming*, 21(5):313–348, October 1992.

[21] Paul Feautrier. Some efficient solutions to the affine scheduling problem, part II: multi-dimensional time. *Int. J. Parallel Programming*, 21(6):389–420, December 1992.

[22] High Performance Fortran Forum. High Performance Fortran Language Specification. Technical Report 2.0, Rice University, January 1997.

[23] Marc Le Fur, Jean-Louis Pazat, and Françoise André. Commutative loop nest distribution. In H.J. Sips, editor, *Proc. of the Fourth Int. Workshop on Compilers for Parallel Computers*, pages 345–350, Delft, The Netherlands, December 1993.

[24] Apostolos Gerasoulis and Tao Yang. On the granularity and clustering of directed acyclic task graphs. *IEEE Trans. Parallel and Distributed Systems*, 4(6):686–701, 1993.

[25] The group of Pr. Lengauer. The loopo project. World Wide Web document, URL: `http://brahms.fmi.uni-passau.de/cl/loopo/index.html`.

[26] François Irigoin, Pierre Jouvelot, and Rémy Triolet. Semantical interprocedural parallelization: an overview of the PIPS project. In *Proceedings of the 1991 ACM International Conference on Supercomputing*, Cologne, Germany, June 1991.

[27] François Irigoin and Rémy Triolet. Computing dependence direction vectors and dependence cones with linear systems. Technical Report ENSMP-CAI-87-E94, Ecole des Mines de Paris, Fontainebleau (France), 1987.

[28] Wayne Kelly, William Pugh, and Evan Rosser. Code generation for multiple mappings. In *The 5th Symposium on Frontiers of Massively Parallel Computation*, pages 332–341, McLean, Virginia, February 1995.

[29] Leslie Lamport. The parallel execution of DO loops. *Communications of the ACM*, 17(2):83–93, February 1974.

[30] Wei Li and Keshav Pingali. A singular loop transformation framework based on non-singular matrices. In *5th Workshop on Languages and Compilers for Parallel Computing*, pages 249–260, Yale University, August 1992.

[31] Amy W. Lim and Monica S. Lam. Maximizing parallelism and minimizing synchronization with affine transforms. In *Proceedings of the 24th Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, January 1997.

[32] Kathryn S. McKinley and Ken Kennedy. Maximizing loop parallelism and improving data locality via loop fusion and distribution. In U. Banerjee, D. Gelernter, A. Nicolau, and D. Padua, editors, *The Sixth Annual Languages and Compiler for Parallelism Workshop*, number 768 in Lecture Notes in Computer Science, pages 301–320. Springer-Verlag, 1993.

[33] C. Picouleau. Two new NP-complete scheduling problems with communication delays and unlimited number of processors. Technical Report 91-24, IBP, Université Pierre et Marie Curie, France, April 1991.

[34] William Pugh. A practical algorithm for exact array dependence analysis. *Communications of the ACM*, 8:27–47, August 1992.

[35] William Pugh and the Omega Team. World Wide Web document, URL: `http://www.cs.umd.edu/projects/omega/`.

[36] Alexander Schrijver. *Theory of Linear and Integer Programming.* John Wiley and Sons, New York, 1986.

[37] Michael E. Wolf and Monica S. Lam. A loop transformation theory and an algorithm to maximize parallelism. *IEEE Trans. Parallel Distributed Systems*, 2(4):452–471, October 1991.

[38] Michael Wolfe. *Optimizing Supercompilers for Supercomputers.* MIT Press, Cambridge MA, 1989.

[39] Michael Wolfe. *High Performance Compilers For Parallel Computing.* Addison-Wesley Publishing Company, 1996.

[40] Jingling Xue. Automatic non-unimodular transformations of loop nests. *Parallel Computing*, 20(5):711–728, May 1994.

[41] Yi-Qing Yang, Corinne Ancourt, and François Irigoin. Minimal data dependence abstractions for loop transformations. *International Journal of Parallel Programming*, 23(4):359–388, August 1995.