





Oritatami: **A computational model for** **cotranscriptional folding**

Nicolas **Schabanel**






CNRS - LIP, ENS Lyon & IXXI - France

Co-transcriptional folding




Geary, Rothmund, Andersen, Science 2014

RNA co-transcriptional folding




Geary, Rothmund, Andersen, Science 2014

Protocol






RNA Origami in Real Time



T7 RNA polymerase produces RNA directionally from 5' to 3', **at a rate much slower than the RNA folds up (few microseconds).**


The polymerase reads the DNA gene, and becomes an RNA origami production factory, **synthesizing a new RNA origami roughly every 1 second.**

AFM imaging of 4H-AE co-transcriptional assembly




RNA Folding

(Real time: ~1 second)



Video: Geary




Oritatami: A computational model for co-transcriptional folding

Geary, Meunier, Schabanel, Seki MFCS 2016

RNA Folding

(Real time: ~1 second)



Oritatami:

A model for co-transcriptional folding

The program:


- a sequence of **bead types** (the **transcript**)

The instructions:

- the rule **a**♥**b** if bead types **a** and **b** attract each other

The input configuration:

- Some beads placed beforehand (the **seed**)




Oritatami:

A model for co-transcriptional folding

The dynamics.

- Starting from the seed, the sequence is *produced one bead at a time*
- **Only the δ last produced beads** are free to move and explore the accessible positions to settle in the ones **maximizing the number of bonds**
- All other beads remain in their last locations




Oritatami:

A model for co-transcriptional folding

The dynamics.

- Starting from the seed, the sequence is *produced one bead at a time*
- **Only the δ last produced beads** are free to move and explore the accessible positions to settle in the ones **maximizing the number of bonds**
- All other beads remain in their last locations




Oritatami:

A model for co-transcriptional folding

The dynamics.

- Starting from the seed, the sequence is *produced one bead at a time*
- **Only the δ last produced beads** are free to move and explore the accessible positions to settle in the ones **maximizing the number of bonds**
- All other beads remain in their last locations




Oritatami:

A model for co-transcriptional folding

The dynamics.

- Starting from the seed, the sequence is *produced one bead at a time*
- **Only the δ last produced beads** are free to move and explore the accessible positions to settle in the ones **maximizing the number of bonds**
- All other beads remain in their last locations



Oritatami:

A model for co-transcriptional folding

The dynamics.

- Starting from the seed, the sequence is *produced one bead at a time*
- **Only the δ last produced beads** are free to move and explore the accessible positions to settle in the ones **maximizing the number of bonds**
- All other beads remain in their last locations



There might be several configurations with max. bonding


Oritatami:

A model for co-transcriptional folding

The dynamics.

- Starting from the seed, the sequence is *produced one bead at a time*
- **Only the δ last produced beads** are free to move and explore the accessible positions to settle in the ones **maximizing the number of bonds**
- All other beads remain in their last locations


The bead has same position in all maximal extension
 $\Rightarrow$ **deterministic**




There might be several configurations with max. bonding

Oritatami: a first construction

here, delay $\delta = 3$




A glider



A switchback

Both can be combined together

Oritatami vs aTAM




Some self-assembly seminal work (mostly aTAM)

- Tile assembly systems are **Turing universal** [Winfree, 1998]
- **Arbitrary shape assembly** with optimal tile set size [Soloveichik, Winfree, 2007]
- **Uncomputable limit configurations** [Lathrop, Lutz, Pattiz, Summers, 2011]
- **Intrinsic universality** [Doty et al, 2012]


Oritatami

- A **binary counter** [Geary, Meunier, S., Seki, 2016]
- Heighdragon **fractal** [Masuda, Seki, Ubukata, 2018]
- Folding **arbitrary shapes** [Demaine et al, 2018]
- **NP-hardness** for oritatami design [Geary et al, 2016; Ota, Seki, 2017; Han, Kim, 2017] and for non-deterministic oritatami equivalence [Han et al, 2016]
- **Efficient Turing Machine simulation** through tag-systems [Geary et al, 2018]
- Intrinsic simulation of **1D cellular automata** [Pchelina et al, 2020]
- Intrinsic simulation of **Turedo: uncomputable** and **arbitrary dense** limit configurations, building **arbitrary object** from asymptotically minimal seed [Pchelina et al, 2022]




Oritatami. A binary counter

Information is encoded in the geometry




Oritatami. A binary counter

Information is encoded in the geometry




Oritatami. A binary counter

Information is encoded in the geometry



How does computation work?





**Oritatami is
Turing complete**


Trimmed space-time diagram

Consider the following productions: $p = \langle \overset{[0]}{1}\overset{[1]}{1}\overset{[2]}{0}, \epsilon, \overset{[2]}{1}\overset{[3]}{1}, \overset{[3]}{0} \rangle$

$$[0]010 \rightarrow [1]10 \xrightarrow{\substack{\text{Append} \\ [2]:11}} [3]011 \rightarrow [0]11 \xrightarrow{\substack{\text{Append} \\ [1]:\epsilon}} [2]1 \xrightarrow{\substack{\text{Append} \\ [3]:0}} [0]0 \rightarrow [1] \text{ Halt}$$








How hard is it to design a molecule and a rule?

27


The first challenge:

Designing the desired shapes


- Design shapes for which a **common** rule ❤️ exists




$$0+0 = 0 + \text{no } C$$



$$1+0 = 1 + \text{no } C$$



$$0+1 = 1 + \text{no } C$$




$$1+1 = 0 + C$$

- Design paths for which a **common** rule ❤️ exists



The first challenge: Designing the paths

- Design paths for which a common rule ❤️ exists




Oritatami design is NP-hard


INPUT:	a delay time δ , a list of $n > 0$ seeds $\sigma_1, \sigma_2, \dots, \sigma_n$, and a list of n conformations $c_1, c_2, \dots, c_n$ of the same length l
OUTPUT:	an attraction rule $\heartsuit$ such that for all $i \in \{1, 2, \dots, n\}$, Oritatami system $\mathcal{O}_i = (s, \sigma_i, \heartsuit, \delta)$ deterministically folds into conformation c_i , where s is the sequence of length l such that for all $i \in \{1, 2, \dots, l\}$, $s_i = i$.

The reduction (*length=1, δ arbitrary*)

Ensures it binds to at least one literal in $l_i \vee l_j \vee l_k$



Ensures it binds to at most one of x_i and $\neg x_i$



The second challenge: Designing the rule


Theorem. There is a **FPT algorithm** with respect to L that designs **in linear time in L** (but exponential in k and δ) a **rule**  that folds the sequence $1, \dots, L$ of length L into k prescribed conformations when folded in k prescribed environments.

Proof. • **Locality:** each bead only sees a bounded number (exponential in δ) of other beads when folded.

- Then, compute all valid local rules for each of these neighborhoods
- And use dynamic programming to decide whether there is a global rule compatible with at least one of the local rule for each environment.


Building shapes

**Goal: Given a shape S ,
Find an oritatami system, i.e. a
sequence of bead types,
that folds into S**




An Oritatami system folds a shape if:

Starting from the seed configuration,
it folds deterministically to occupy all the positions of
the shape and only them





Seek an Universal construction


- **Fixed** finite size seed
- **Fixed** finite set of bead types
(independent of the shape)




Example of such molecule



Trivial fact: Foldable shapes are Hamiltonian




Fact: Finitely cuttable *infinite* shapes cannot be folded



A **finite set of points** cutting the shape into several infinite pieces

Fact: Finitely cuttable *infinite* shapes cannot be folded





A **finite set of points** cutting the shape into several infinite pieces


Oritatami systems are thus essentially different from tile assembly systems (aTam)

**Consider
upscaling schemes**

Upscaling schemes





scale $\mathcal{A}_n, n = 3$




scale $\mathcal{B}_n, n = 3$

Finite shapes are Hamiltonian at scale $\mathcal{A}_2$


Theorem. There is a quadratic algorithm that computes an Hamiltonian path for any finite shape at scale $\mathcal{A}_2$



Upscaling does not help with finitely cuttable infinite shapes




Upscaling does not help with finitely cuttable infinite shapes



Thus, we focus on **finite shapes**

Scale $\mathcal{B}_n$


scale $\mathcal{B}_n$



Use a unique pattern



scale $\mathcal{B}_n$



Use a unique pattern




scale $\mathcal{B}_n$

Use a unique pattern

Theorem. All finite shapes can be folded at scale $\mathcal{B}_n$ for $n \geq 3$


Proof. By induction:

For **all red edges**, the corresponding **three purple positions** are filled before.



**How many bead
types are needed?**

Affine coloring of hexagons



Theorem. Let H_n be the hexagon of radius n ,


$$c(i,j) = ni + (n+1)j \bmod |H_n|$$

is a proper coloring of H_n

Corolary 1. As it is affine, it is a proper coloring of *any* translation of H_n

Corolary 2. Furthermore, the colors of the neighbors of a given node are fixed translations modulo $|H_n|$ of its own color

Affine coloring of hexagons



Theorem. Let H_n be the hexagon of radius n ,

$$c(i,j) = ni + (n+1)j \bmod |H_n|$$

is a proper coloring of H_n


Corollary 1. As it is affine, it is a proper coloring of *any* translation of H_n

Corollary 2. Furthermore, the colors of the neighbors of a given node are fixed translations modulo $|H_n|$ of its own color

Tight oritatami Systems

An oritatami system is *tight* if:

- delay $\delta = 1$
- **every bead destination has a tight neighbor**, i.e. such that there is only **one available position** next to it




For tight oritatami system, each bead's position is uniquely determined by whom it is attracted to

Tight oritatami Systems


An oritatami system is *tight* if:

- delay $\delta = 1$
- **every bead destination has a tight neighbor**, i.e. such that there is only **one available position** next to it



For tight oritatami system, each bead's position is uniquely determined by whom it is attracted to

19 bead types are enough for tight oritatami systems



Each bead located at (i,j)
receives bead type:


$$c(i, j)$$

and $c \heartsuit c'$ iff

$$c' = c + \Delta c(d) \bmod 19$$

For tight oritatami system, each bead's position is fully determined by whom it is attracted to

19 bead types are enough for tight oritatami systems



Each bead located at (i, j) receives bead type:


$$c(i, j)$$

and $c \heartsuit c'$ iff

$$c' = c + \Delta c(d) \bmod 19$$

Theorem. 19 beads types are enough

19 bead types are enough for tight oritatami systems




Each bead located at (i, j)
receives bead type:

$$c(i, j)$$


and $c \heartsuit c'$ iff

$$c' = c + \Delta c(d) \bmod 19$$



Theorem. 19 beads types are enough

19 bead types are enough for tight oritatami systems




Each bead located at (i, j) receives bead type:

$$c(i, j)$$

and $c \heartsuit c'$ iff


$$c' = c + \Delta c(d) \bmod 19$$



Theorem. There is a **constant-time incremental** algorithm that outputs a tight oritatami system using **19 bead types** that folds any finite shape at scale $\mathcal{B}_n \geq 3$ from a **seed of size 3**

Would increasing the delay instead of upscaling help?

Theorem. For any delay δ , there is an infinite shape that cannot be folded by no oritatami system with delay δ



Turedo: building nanobots with oritatami



[Pchelina, S., Seki and Theyssier, *STACS* 2022]

Turedo

A finite automata follows a **self-avoiding path**, moving and **writing** a state according to a **uniform local rule**



A clockwise walker

The rule:




Radius-1 Turedos implement cellular automata


Left/Right Swiping
The rule:



Theorem 1.

Radius-1 turedos doodle uncomputably




The background of the slide is a complex geometric pattern. It features a grid of white hexagons separated by light blue channels. Within these channels, there are intricate, winding paths drawn in orange and purple. Some paths are straight, while others are highly convoluted, resembling a maze. There are also small, rectangular blocks of color (green, blue, orange) placed at various points along the paths. Four large, grey, hand-drawn arrows point towards the center of the slide from the top, bottom, left, and right edges.

**Delay-3 Oritatami systems simulate
radius-1 Turedos intrinsically**

Intrinsic simulation

- Linear time & scape rescaling





Brice Due 2006

The Game of Life self-simulating itself intrinsically:
Smaller cells simulate macro-cells


Oritatami systems simulate 1D CA intrinsically

- **Previous work.** [PSSU, 2020]
1D Cellular automata intrinsic simulation




2 Problems. Macrocells must be isotropic
We need to **exit from an arbitrary side...**

the Macrocell



Bit-weighted encoding for Turedos



- **Turedo**

$Q = 2^q - 1$ states and the empty state $\perp$

Transition function:

$$F : (Q \cup \{\perp\})^6 \rightarrow Q \times \{\leftarrow, \nearrow, \nearrow, \rightarrow, \searrow, \swarrow\}$$

$$(x_0, \dots, x_5) \mapsto (y, d)$$


- **Bit-weight encoding**

w_{ij} = weight of the j -th bit x_{ij} of x_i


$$F(x) = \Phi(w(x)) \text{ where } w(x) = \sum_{ij} w_{ij} x_{ij}$$

- $w_{ij} = 2^{qi+j}$ works for all F


the Macrocell



the Macrocell




Reading. Reading pockets




If j -th bit = 1, then Shift += w_{ij}
 $\Rightarrow$ Shift on i -th side = $\sum_j w_{ij} x_{ij} = w(x_i)$
 $\Rightarrow$ **Total Shift on all side = $w(x)$**

Uturn pocket. Read to write




the Macrocell



Writing. Shift pushes the transition table to the right

bits 0 and 1 fold differently




The pockets hide the $W = \sum_{ij} w_{ij}$
unused entries in the transition table



Writing. Shift pushes the transition table to the right

bits 0 and 1 fold differently


⇒ the exit layer shows or hide the special beads




The pockets hide the $W = \sum_{ij} w_{ij}$
unused entries in the transition table




the Macrocell




Resynchronizing. Speedbumps [PSSU2020]



**Can absorb
any offset $\leq W$
(in Zig-Zags! 🙄)**



the Macrocell




Exiting... or not




By default, **exit layer** follows the border of the exit box

Exiting... or not



With the proper signal (offset!), **exit layer** folds upon itself and... **exit!**


Key new tool: Folding meter



it folds upon itself into pockets



Suspiciously simple fact

All layers stay synchronized




Almost there

1



Read pocket


Almost there





Exit sliding pocket

Almost there


Curvy speedbump




Almost there





Almost there



Almost there





Theorem 2. Delay-3 oritatami simulates intrinsically radius-1 turedos




Example: A bouncy right hand turedo

Some examples



A Sierpinsky turedo

The background of the slide features a complex geometric pattern. It consists of several large, irregular red polygons that are interconnected by a network of thin, jagged lines. These lines are primarily yellow and orange, with some segments in a light purple or blue color. The overall effect is a dense, crystalline or cellular structure. The text is centered over this pattern.


The density of limit configurations

Theorem 3. The densities of radius-1 Turedos limit configuration are all Π_2

$$\limsup_n q_n = q \in \Pi_2$$

Next annulus erases previous one by computing R_n such that:


$$(R_{n+1})^2 q_{n+1} \gg (R_n)^2 q_n$$





Fact. The densities of limit configurations for directed aTAM and freezing cellular automata belong to Π_2 also.

Corollary. The densities of oritatami limit configuration are all Π_2

Must beware of the **rotation induced** by the oritatami simulation





Oritatami world
The target balls




Turedo world
The simulated balls

Corollary. The densities of oritatami limit configuration are all Π_2

Fill a hardcoded hexagon in the center of an extended macrocell



Conclusion



- **No need for parallelism**
- **No need for 3D**
- Lines just don't cross!
- We have a running implementation:
<https://hub.darcs.net/turedo2oritatami/turedo2oritatami/>
- New tools for Oritatami: **Folding meter, pockets, distant sensor & crazy-curvy speedbump, and... Turedo!**
- Some interesting turedos implemented in oritatami and... RNA ?
e.g.: **simple plane filling oritatami**
- **What about turedos ?** → S. Nalin & G. Theyssier (*coming soon*)